

COMMERCIAL DEFROST CONTROLS

Paragon

Defrost Controls

Time initiated, time terminated, 40 amp.

FEATURES:

- Adjustable frequency defrost from 1 – 6 cycle per day. Min. 4 hours between successive operations.
- Adjustable duration of defrost cycle from 4 – 110 min. in 2 min. increments.
- Defrost duration accurate to ± 2 min.
- Positive switch action slider bar.
- Switch rating per pole: 40 amps, 2 hp per pole, 690 va pilot duty, 120-240 volts AC.
- Heavy-duty, synchronous, industrial type motor.



8041 SERIES - FOR ELECTRIC HEAT DEFROSTING - AUXILIARY CONTACT MODELS

Switch Contact Arrangement	Volts @ 60 Hz	Replaces	Mfr#	New Item#	Reman#
2 - 4 close, 1 - 3 open, 3 - N close	120	---	8041-00	C255-110	C255-110R
Same as above	208/240	---	8041-20	C255-112	C255-112R

8045 SERIES - FOR ELECTRIC HEAT, HOT GAS OR COMPRESSOR SHUTDOWN DEFROSTING

2 - 4 close, 1 - 3 open, 3 - N none	120	305-MB, 8005, 8015-0	8045-00	C255-118	C255-118R
Same as above	208/240	306-MB, 8006, 8015-3	8045-20	C255-120	C255-120R

8047 SERIES - FOR ELECTRIC HEAT DEFROSTING - AUXILIARY CONTACT MODELS

2 - 4 open, 1 - 3 open, 3 - N close	120	8007, 8017-0	8047-00	C255-122	C255-122R
Same as above	208/240	8008, 8017-3	8047-20		C255-124R

Note: Remanufactured products available only on exchange for similar defective units.