- The combination of the rubber-resin adhesive and the flame-retardant, PVC backing offers electrical and mechanical protection
- Withstands a temperature range of 32 to 176 °F (0 to 80 °C)
- Made of durable PVC
- UL Listed, ASTM Approved, CSA Certified and RoHS 2011/65/EU Compliant

\#

Specifications

Adhesive Type	**Rubber**
Brand	**Temflex™**
Color Family	**Purple**
Overall Length (Imperial)	**66 ft**
Overall Length (Metric)	**20.1 m**
Overall Width (Imperial)	**0.75 in, 1.5 in**
Overall Width (Metric)	**19 mm, 38 mm**
Product Color	**Blue, Brown, Gray, Green, Orange, Red, Violet, White, Yellow**

Details

- The combination of the rubber-resin adhesive and the flame-retardant, PVC backing offers electrical and mechanical protection
- Withstands a temperature range of 32 to 176 °F (0 to 80 °C)
- Made of durable PVC
- UL Listed, ASTM Approved, CSA Certified and RoHS 2011/65/EU Compliant

3M™ Temflex™ Electrical Tape 1700C is a 7 mil thick, general purpose, vinyl electrical tape. This flame retardant tape is designed for protective jacketing and harnessing. This tape is 600V rated and withstands a temperature range of 32 to 176 °F (0 to 80 °C).

\#