Three Phase MOJAVE® Series Commercial Condenser Fan Open Drip Proof, Air Over

APPLICATIONS:

Designed to meet manufacturer's requirements for condenser cooling fans in commercial air conditioning applications where 3 phase power id required.

ADDITIONAL FEATURES to MOJAVE® Series:

- 158°F (70°C) Ambient Design
- 208v will not be marked on DOE regulated spread-voltage motors.
 Refer to online data
- · Discount Symbol: DS-3HAC

Belly Band Mount, Flat and Keyway on Shaft

НР	RPM/Spds	Voltage	Catalog Number	List	NEMA Frame	Amps	Shaft N	Shell XI	Total C	Shaft Dia.	Ship Wt.	Notes
3/4	1140	208-230/460	1817H	+	56Z	2.8/1.4	6.0	9.3	15.3	0.625	31.5	
1	850	208-230/460	1828H	+	56Z	4.8/2.4	6.0	.625	16.8	0.625	40	
	850	575	1829H	+	56Z	1.7	6.0	10.8	16.8	0.625	41	
	1140	208-230/460	1818H	+	56Z	4.2/2.1	6.0	.625	14.8	0.625	27.3	
1 1/2	850	208-230/460	1832H	+	56Z	6.8/3.3	6.0	10.8	16.8	0.625	44.1	
	1140	208-230/460	1819H	+	56Z	5.4/2.7	6.0	.625	15.8	0.625	35	
2	1140	208-230/460	8987H	*	56Z	7.6/3.7	6.0	10.8	16.8	0.625	45	

Rigid Base Mount, Flat and Keyway on Shaft

НР	RPM/ Spds	Voltage	Catalog Number	List	NEMA Frame	Amps	Shaft N	Shell XI	Total C	Shaft Dia.	Ship Wt.	Notes
3/4	1140	208-230/460	1826H	+	56Z	2.8/1.4	6.0	9.3	15.3	0.625	31.5	
1	850	208-230/460	1833H	+	56Z	4.8/2.4	6.0	10.8	16.8	0.625	31.5	
	1140	208-230/460	1820H	+	56Z	4.2/2.1	6.0	.625	14.8	0.625	27	
1 1/2	850	208-230/460	1831H	+	56Z	6.8/3.3	6.0	10.8	16.8	0.625	44.1	
	1140	208-230/460	1821H	+	56Z	5.4/2.7	6.0	.625	15.8	0.625	35	
2	1140	208-230/460	1822H	+	56Z	7.6-7.4/3.7	6.0	.625	16.8	0.625	45	

◆ Refer to Motorboss for Pricing

