



EZ13[®]

UNIVERSAL ECM REPLACEMENT
FOR FURNACES AND AIR HANDLERS



Truck Stock



Universal Replacement



Ready to Install



Replaces Thousands
of OEM Models

Improved
Reliability With:



Built-in 6,000 Volt
surge protection



Industry-leading
moisture protection



SPECIFICATIONS

HORSEPOWER: 1/3-1/2, 3/4 AND 1 HP

VOLTAGE: 1Ø, 115, 208-230 Vac

SPEEDS: 1075/Var

ROTATION: Auto-Rotation Sensing

INPUTS: 24Vac, Tap Inputs

HERTZ: 50/60 Hz


OPERATION MODE: Constant Torque

FRAME: NEMA® 48

ENCLOSURE: Open Air Over (OAO)

EFFICIENCY: Up to 82%

MOUNTING: Belly-band



CATALOG NUMBER	HP	VOLTS	AMPS	RPM	DIM. A	DIM. B
5632	1/2 -1/3	115/208-230	6.3/4.0-3.8	1075/Var	3.662	11.225
5642	3/4	115/208-230	9.3/5.8-5.4	1075/Var	4.037	11.600
5652	1	115/208-230	12.4/7.8-7.2	1075/Var	4.412	11.975



8050 W. Florissant Avenue | St. Louis, MO 63136
Phone: 855-487-6686 | Fax: 800-899-2887

© Nidec 2021; All Rights Reserved.

21-8526-01 EZ13 PDS

Scan to watch
RESCUE EZ13
Overview Training Video

