

## Definite Purpose Contactors



### Features

Contactors meet UL508 specifications for devices up to 600 Vac.

- 50/60 Hertz •
- Coils have class B insulation
- Includes lugs, spade terminals and covers
- All single pole include shunt



| Item ID               | Poles | F/L Inductive Amps | Locked Rotor Amps 240/480/600 | Resistive Amps | Coil Voltage |
|-----------------------|-------|--------------------|-------------------------------|----------------|--------------|
| <b>Packard 1 Pole</b> |       |                    |                               |                |              |
| C125A                 | 1+    | 25                 | 150/125/100                   | 30             | 24           |
| C125B                 | 1+    | 25                 | 150/125/100                   | 30             | 120          |
| C125C                 | 1+    | 25                 | 150/125/100                   | 30             | 208/240      |
| C130A                 | 1+    | 30                 | 180/150/120                   | 40             | 24           |
| C130B                 | 1+    | 30                 | 180/150/120                   | 40             | 120          |
| C130C                 | 1+    | 30                 | 180/150/120                   | 40             | 208/240      |
| C140A                 | 1+    | 40                 | 240/200/160                   | 50             | 24           |
| C140B                 | 1+    | 40                 | 240/200/160                   | 50             | 120          |
| C140C                 | 1+    | 40                 | 240/200/160                   | 50             | 208/240      |
| <b>Packard 2 Pole</b> |       |                    |                               |                |              |
| C220A                 | 2     | 20                 | 120/100/80                    | 30             | 24           |
| C220B                 | 2     | 20                 | 120/100/80                    | 30             | 120          |
| C220C                 | 2     | 20                 | 120/100/80                    | 30             | 208/240      |
| C225A                 | 2     | 25                 | 150/125/100                   | 35             | 24           |
| C225B                 | 2     | 25                 | 150/125/100                   | 35             | 120          |
| C225C                 | 2     | 25                 | 150/125/100                   | 35             | 208/240      |
| C230A                 | 2     | 30                 | 180/150/120                   | 40             | 24           |
| C230B                 | 2     | 30                 | 180/150/120                   | 40             | 120          |
| C230C                 | 2     | 30                 | 180/150/120                   | 40             | 208/240      |
| C230D*                | 2     | 30                 | 180/150/120                   | 40             | 208/240      |
| C230E                 | 2     | 30                 | 180/150/120                   | 40             | 277          |
| C240A                 | 2     | 40                 | 240/200/160                   | 50             | 24           |
| C240B                 | 2     | 40                 | 240/200/160                   | 50             | 120          |
| C240C                 | 2     | 40                 | 240/200/160                   | 50             | 208/240      |
| C240E                 | 2     | 40                 | 240/200/160                   | 50             | 277          |

| Item ID               | Poles | F/L Inductive Amps | Locked Rotor Amps 240/480/600 | Resistive Amps | Coil Voltage | Aux. Switch   |
|-----------------------|-------|--------------------|-------------------------------|----------------|--------------|---------------|
| <b>Packard 3 Pole</b> |       |                    |                               |                |              |               |
| C325A                 | 3     | 25                 | 150/125/100                   | 35             | 24           | AC3           |
| C325B                 | 3     | 25                 | 150/125/100                   | 35             | 120          | AC3           |
| C325C                 | 3     | 25                 | 150/125/100                   | 35             | 208/240      | AC3           |
| C330A                 | 3     | 30                 | 180/150/120                   | 40             | 24           | AC3, P6S, P7S |
| C330B                 | 3     | 30                 | 180/150/120                   | 40             | 120          | AC3, P6S, P7S |
| C330C                 | 3     | 30                 | 180/150/120                   | 40             | 208/240      | AC3, P6S, P7S |
| C330E                 | 3     | 30                 | 180/150/120                   | 40             | 277          | AC3, P6S, P7S |
| C330F                 | 3     | 30                 | 180/150/120                   | 40             | 480          | AC3, P6S, P7S |
| C340A                 | 3     | 40                 | 240/200/160                   | 50             | 24           | AC3, P6S, P7S |
| C340B                 | 3     | 40                 | 240/200/160                   | 50             | 120          | AC3, P6S, P7S |
| C340C                 | 3     | 40                 | 240/200/160                   | 50             | 208/240      | AC3, P6S, P7S |
| C340E                 | 3     | 40                 | 240/200/160                   | 50             | 277          | AC3, P6S, P7S |
| C340F                 | 3     | 40                 | 240/200/160                   | 50             | 480          | AC3, P6S, P7S |
| C350A                 | 3     | 50                 | 300/250/200                   | 65             | 24           | P8S, P38K     |
| C350B                 | 3     | 50                 | 300/250/200                   | 65             | 120          | P8S, P38K     |
| C350C                 | 3     | 50                 | 300/250/200                   | 65             | 208/240      | P8S, P38K     |
| C350F                 | 3     | 50                 | 300/250/200                   | 65             | 480          | P8S, P38K     |
| C360A                 | 3     | 60                 | 360/300/240                   | 75             | 24           | P8S, P38K     |
| C360B                 | 3     | 60                 | 360/300/240                   | 75             | 120          | P8S, P38K     |
| C360C                 | 3     | 60                 | 360/300/240                   | 75             | 208/240      | P8S, P38K     |
| C360F                 | 3     | 60                 | 360/300/240                   | 75             | 480          | P8S, P38K     |
| C375A                 | 3     | 75                 | 450/375/300                   | 90             | 24           | P9S           |
| C375B                 | 3     | 75                 | 450/375/300                   | 90             | 120          | P9S           |
| C375C                 | 3     | 75                 | 450/375/300                   | 90             | 208/240      | P9S           |
| C390A                 | 3     | 90                 | 540/450/360                   | 120            | 24           | P9S           |
| C390B                 | 3     | 90                 | 540/450/360                   | 120            | 120          | P9S           |
| C390C                 | 3     | 90                 | 540/450/360                   | 120            | 208/240      | P9S           |
| <b>Packard 4 Pole</b> |       |                    |                               |                |              |               |
| C430A                 | 4     | 30                 | 180/150/120                   | 40             | 24           | AC3, P6S, P7S |
| C430B                 | 4     | 30                 | 180/150/120                   | 40             | 120          | AC3, P6S, P7S |
| C430C                 | 4     | 30                 | 180/150/120                   | 40             | 208/240      | AC3, P6S, P7S |
| C430F                 | 4     | 30                 | 180/150/120                   | 40             | 480          | AC3, P6S, P7S |
| C440A                 | 4     | 40                 | 240/200/160                   | 50             | 24           | AC3, P6S, P7S |
| C440B                 | 4     | 40                 | 240/200/160                   | 50             | 120          | AC3, P6S, P7S |
| C440C                 | 4     | 40                 | 240/200/160                   | 50             | 208/240      | AC3, P6S, P7S |
| C440F                 | 4     | 40                 | 240/200/160                   | 50             | 480          | AC3, P6S, P7S |

Notes:  
\* Spade terminals and cover only.  
Auxiliary Switches sold separately. See page 226.

## Magnetic Contactor



| Item ID                    | C18001    |
|----------------------------|-----------|
| Type                       | DPST N.O. |
| Resistive Amps             | 30        |
| Full Load Amps             | 30        |
| Locked Rotor Amps          | 120       |
| Coil Voltage               | 24        |
| Hertz                      | 50/60     |
| Max. Surrounding Air Temp. | 40°C      |
| Phase                      | Single    |

### Replaces

|         |           |       |
|---------|-----------|-------|
| 3ARR8E4 | MC11      | 18001 |
| 90-230  | R850B1146 |       |

## DP Contactor



| Item ID            | PR4013 |
|--------------------|--------|
| F/L Inductive Amps | 30     |
| Poles              | 1      |
| Resistive Amps     | 40     |
| Coil Voltage       | 24     |

### Replaces

DP1030A5013