

CHECK VALVES | BRASS & PLASTIC



Stop & Waste Valve
CPVC

| Item No. | Size | Connection | Inner | MC |
|-----------|------|-------------|-------|----|
| 105-323 | 1/2" | SLIP x SLIP | 12 | 72 |
| 105-323HN | 1/2" | SLIP x SLIP | - | 20 |
| 105-324 | 3/4" | SLIP x SLIP | 12 | 72 |
| 105-324HN | 3/4" | SLIP x SLIP | - | 20 |

Features:

- Rated for 100 PSI @ 180°F
- Rising stem for positive open and close operation
- For use with hot or cold water
- Not for use with compressed air
- Solvent connection for use with CPVC tubing size pipe
- Plug allows draining of non-pressure side of valve when closed



Swing Check Valve
Brass | Hard Seat
Threaded

| Item No. | Size | Connection | Inner | MC |
|-----------|--------|------------|-------|-----|
| 101-001NL | 1/4" | FIP x FIP | 10 | 100 |
| 101-002NL | 3/8" | FIP x FIP | 10 | 100 |
| 101-003NL | 1/2" | FIP x FIP | - | 15 |
| 101-004NL | 3/4" | FIP x FIP | - | 15 |
| 101-005NL | 1" | FIP x FIP | 5 | 40 |
| 101-006NL | 1-1/4" | FIP x FIP | 5 | 30 |
| 101-007NL | 1-1/2" | FIP x FIP | 4 | 24 |
| 101-008NL | 2" | FIP x FIP | 2 | 16 |
| 101-009NL | 2-1/2" | FIP x FIP | - | - |
| 101-010NL | 3" | FIP x FIP | - | - |

Features:

- 200 PSI WOA



Swing Check Valve
Brass | Hard Seat
Solder

| Item No. | Size | Connection | Inner | MC |
|-----------|--------|------------|-------|----|
| 101-503NL | 1/2" | C x C | - | 15 |
| 101-504NL | 3/4" | C x C | - | 15 |
| 101-505NL | 1" | C x C | 5 | 40 |
| 101-506NL | 1-1/4" | C x C | 5 | 30 |
| 101-507NL | 1-1/2" | C x C | 4 | 24 |
| 101-508NL | 2" | C x C | 2 | 16 |
| 101-509NL | 2-1/2" | C x C | - | - |
| 101-510NL | 3" | C x C | - | - |

Features:

- 200 PSI WOA



Swing Check Valve
Bronze | "Y" Pattern
Threaded

| Item No. | Size | Connection | Inner | MC |
|----------|--------|------------|-------|-----|
| 101-203 | 1/2" | FIP x FIP | 10 | 120 |
| 101-204 | 3/4" | FIP x FIP | 10 | 80 |
| 101-205 | 1" | FIP x FIP | 10 | 60 |
| 101-206 | 1-1/4" | FIP x FIP | 5 | 30 |
| 101-207 | 1-1/2" | FIP x FIP | 4 | 24 |
| 101-208 | 2" | FIP x FIP | 2 | 16 |

Features:

- 300 PSI non-shock WOG
- 150 PSI working steam pressure
- Heavy bronze construction
- Screw-on cap
- Swing-type disc with integral seat
- PTFE face on disc for positive seal
- Vertical or horizontal installation