



SECTION 02 GAS VALVES

ProLine Gas Valves are precisely engineered for outsanding service, long life and reliable performance to ensure a safe gas flow control line. All valves are designed with safety in mind and offer a quarter turn with some even offering a safety handle to ensure intentional gas flow control. Tested to the highest standards, ProLine Gas Valves will ensure the job stays safe.

Gas Valves012

- One Piece Bodies
- Two Piece Bodies
- SureOff

Log Lighters016

- Straight
- Angle

GAS VALVES | BRASS VALVES





Gas Ball Valve

Forged Brass | Italian One Piece Body | Lever Handle

| Item No. | Size | Connection | Inner | МС |
|-----------|------|------------|-------|-----|
| 110-522 | 3/8" | FIP x FIP | 10 | 100 |
| 110-522HC | 3/8" | FIP x FIP | - | 10 |
| 110-523 | 1/2" | FIP x FIP | 10 | 100 |
| 110-523HC | 1/2" | FIP x FIP | - | 30 |
| 110-524 | 3/4" | FIP x FIP | 10 | 100 |
| 110-524HC | 3/4" | FIP x FIP | - | 20 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F to 300°F temperature range
- · Quarter-turn lever handle for positive on/off operation
- · Coated aluminum handle for corrosion and solvent resistance
- · Multi-directional flow
- One-piece body for leak resistance and long valve life
- · Chrome plated brass ball
- · Made in Italy



Gas Ball Valve

Forged Brass | Italian One Piece Body | Tee Handle

| Item No. | Size | Connection | Inner | МС |
|----------|------|------------|-------|-----|
| 111-523 | 1/2" | FIP x FIP | 10 | 100 |
| 111-524 | 3/4" | FIP x FIP | 10 | 100 |
| 111-525 | 1" | FIP x FIP | 6 | 30 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F 300°F temperature range
- T-handle provides easy-to-turn operation
- · Coated aluminum handle for corrosion and solvent resistance





- · Multi-directional flow
- · One-piece body for leak resistance and long valve life
- · Chrome plated brass ball
- · Made in Italy







Gas Ball Valve

Forged Brass | Italian One Piece Body | Square Head

| Item No. | Size | Connection | Inner | МС |
|-----------|--------|------------|-------|-----|
| 113-523 | 1/2" | FIP x FIP | 10 | 100 |
| 113-523HN | 1/2" | FIP x FIP | - | 12 |
| 113-524 | 3/4" | FIP x FIP | 10 | 100 |
| 113-524HN | 3/4" | FIP x FIP | - | 10 |
| 113-525 | 1" | FIP x FIP | 6 | 30 |
| 113-526 | 1-1/4" | FIP x FIP | 4 | 20 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -10°F 300°F temperature range
- · Flat head operation prevents unintentional operation valve
- · Coated aluminum for corrosion & solvent resistance





| Item No. | Size | Connection | Inner | МС |
|-----------|---------|------------|-------|-----|
| 113-523 | 1/2" | FIP x FIP | 10 | 100 |
| 113-523HN | 1/2" | FIP x FIP | - | 12 |
| 113-524 | 3/4" | FIP x FIP | 10 | 100 |
| 113-524HN | 3/4" | FIP x FIP | - | 10 |
| 113-525 | 1" | FIP x FIP | 6 | 30 |
| 113-526 | 1_1///" | FID v FID | 1 | 20 |

· Multi-directional flow

- · One-piece body for leak resistance and long valve life
- · Chrome plated brass ball
- · Made in Italy



Gas Ball Valve

Forged Brass | Italian One Piece Body | Side Tap

| Item No. | Size | Connection | Inner | МС |
|-----------|------|------------|-------|-----|
| 110-553 | 1/2" | FIP x FIP | 10 | 100 |
| 110-553HN | 3/4" | FIP x FIP | 10 | 100 |
| 110-554 | 1" | FIP x FIP | 6 | 30 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -10°F 300°F temperature range
- · Quarter-turn lever handle for positive on/off operation
- · Coated aluminum for corrosion & solvent resistance





· Multi-directional flow

- · One-piece body for leak resistance and long valve life
- · Chrome plated brass ball
- · Made in Italy







Gas Ball Valve - Side

Forged Brass | Italian One Piece Body

| Item No. | Size | Connection | Inner | MC |
|----------|------|--------------------|-------|-----|
| 116-552 | 3/8" | FL x FL & Side Tap | 10 | 100 |
| 116-553 | 1/2" | FL x FL & Side Tap | 10 | 100 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20F 300F temperature range
- One-piece body for leak resistance and long valve life



- · Coated aluminum handle for corrosion & solvent resistance
- · Chrome plated brass ball
- Made in Italy



Gas Ball Valve Forged Brass | Italian One Piece Body

| Item No. | Size | Connection | Inner | МС |
|----------|-------------|------------|-------|-----|
| 116-502 | 3/8" | FL x FL | 10 | 100 |
| 116-503 | 1/2" | FL x FL | 10 | 100 |
| 116-504 | 5/8" | FL x FL | 10 | 100 |
| 116-512 | 3/8" x 1/2" | FL x MIP | 10 | 100 |
| 116-513 | 1/2" x 1/2" | FL x MIP | 10 | 100 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20F 300F temperature range
- One-piece body for leak resistance and long valve life
- Coated aluminum handle for corrosion & solvent resistance
- · Chrome plated brass ball
- · Made in Italy





Gas Ball Valve - Angle Forged Brass | Italian One Piece Body

| Item No. | Size | Connection | Inner | МС |
|----------|---------------|-----------------|-------|-----|
| 114-533 | 3/8" x 1/2" | FL x FIP, Angle | 10 | 100 |
| 114-534 | 15/16" x 3/4" | FL x FIP, Angle | 10 | 100 |

Feature

- 200 PSI
- 1/2 PSIG and 5G certified
- -20F 300F temperature range
- · One-piece body for leak resistance and long valve life



| es: | |
|-----|--|
| | Coated aluminum handle for |

· Chrome plated brass ball

corrosion & solvent resistance

Made in Italy



Gas Ball Valve - Straight Forged Brass | Italian One Piece Body

| Item No. | Size | Connection | Inner | MC |
|----------|---------------|--------------------|-------|-----|
| 114-522 | 3/8" x 1/2" | FL x FIP, Straight | 10 | 100 |
| 114-523 | 1/2" | FL x FIP, Straight | 10 | 100 |
| 114-544 | 1/2" x 3/4" | FL x FIP, Straight | 10 | 100 |
| 114-543 | 15/16" x 1/2" | FL x FIP, Straight | 10 | 100 |
| 114-524 | 15/16" x 3/4" | FL x FIP, Straight | 10 | 100 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20F 300F temperature range
- · One-piece body for leak resistance and long valve life
- · Coated aluminum handle for corrosion & solvent resistance
- · Chrome plated brass ball
- · Made in Italy



GAS VALVES | BRASS VALVES





Gas Ball Valve

Forged Brass | Italian Two Piece Body | Lever Handle

| Item No. | Size | Connection | Inner | МС |
|-----------|------|------------|-------|-----|
| 110-122 | 3/8" | FIP x FIP | 10 | 100 |
| 110-123HC | 1/2" | FIP x FIP | - | 20 |
| 110-124HC | 3/4" | FIP x FIP | - | 10 |
| 110-125 | 1" | FIP x FIP | 6 | 20 |
| 110-125HC | 1" | FIP x FIP | - | 10 |

Features:

- 200 PSI
- 1/2 PSIG and 5G certified
- -20°F 300°F temperature range
- Quarter turn lever handle for positive on/off operation
- · Coated aluminum handle for corrosion & solvent resistance





- · Multi-directional flow
- Two-piece body design
- · Chrome plated brass ball
- · Made in Italy



Gas Ball Valve

Forged Brass Two Piece Body | Lever Handle

| Item No. | Size | Connection | Inner | MC |
|-----------|------|------------|-------|-----|
| 110-222 | 3/8" | FIP x FIP | 10 | 100 |
| 110-223C | 1/2" | FIP x FIP | 10 | 100 |
| 110-223HC | 1/2" | FIP x FIP | - | 30 |
| 110-224C | 3/4" | FIP x FIP | 10 | 100 |
| 110-224HC | 3/4" | FIP x FIP | - | 20 |
| 110-225 | 1" | FIP x FIP | 6 | 36 |

Features:

- 175 PSI
- 1/2 PSIG and 5G certified
- -20°F 300°F temperature range
- Quarter turn lever handle for positive on/off operation
- · Coated aluminum handle for corrosion & solvent resistance





- · Multi-directional flow
- Two-piece body design
- · Chrome plated brass ball



Gas Ball Valve

Forged Brass | Italian Two Piece Body | Tee Handle

| Item No. | Size | Connection | Inner | мс |
|-----------|------|------------|-------|----|
| 111-123HC | 1/2" | FIP x FIP | - | 25 |
| 111-124HC | 3/4" | FIP x FIP | - | 25 |

Features:

- 1/2 PSIG and 5G certified
- -20°F 300°F temperature range
- T-handle provides easy-to-turn operation
- · Coated aluminum handle for corrosion & solvent resistance

- · Multi-directional flow
- Two-piece body design
- · Chrome plated brass ball
- · Made in Italy