## SERIES 41 MANIFOLDS °F and °C with 3-1/8" (80 mm) gauges



Manifold comes standard with certified gauges.

For more information on the certification of 3-1/8" gauges, see Gauges section.

Series 41 manifolds are also available with larger, easier to read 3-1/8" color-coded gauges in rugged steel cases with polycarbonate crystals. These gauges feature 1% accuracy (Class 1) for an exact reading in critical charge systems.

- Color-coded scales
- Sliding double "O" ring pistons reduce wear
- Long life nylon seats
- Forged brass body for durability
- Full porting maximizes capacity and flow
- Some models include color-coded, 60"
  PLUS II<sup>™</sup> hoses with standard 1/4" flare fittings
- Hose assemblies UL recognized for 4000 psi (275 bar) burst and 800 psi (55 bar) working pressure. File# SA9737
- Made in the USA

	Box	Clamshell			
	UPC#	UPC#	Description - °F/°C	Scale	Refrigerant
	41863	-	Manifold only with 5/16"-1/4"-5/16" anchor fittings and 1/4" service fittings - red/blue gauge	kPa/psi	
	41652	-	Manifold only with 5/16", 1/4", 5/16" anchor and 1/4" service fittings	bar/psi	
	41659	-	Manifold only with 5/16" anchor fittings	bar/psi	D 00/4404
	_	42021 42024	Manifold only Manifold with 60" PLUS II™ standard fittings	bar/psi bar/psi	R-32/410A
	41862	-	Manifold only with 5/16" anchor and	kPa/psi	A2L
		41865	service fittings 41862 with 60" PLUS II™ 5/16" fittings	kPa/psi	COMPATIBLE
	UPC#	UPC#	Description - °F - Red/Blue	Scale	Refrigerant
	-	41842	Manifold only	psi	Tienigerant
	_	42007	Manifold with 60" PLUS II <sup>™</sup> standard fittings	psi	B-12/22/134a
	_	41846	Manifold with 72" PLUS II <sup>™</sup> with couplers	psi	
	-	42001	Manifold only	psi	
	-	49271*	Certified 42001 manifold		
	-	42004	Manifold with 60" PLUS II <sup>™</sup> standard fittings	psi	R-22/404A/410A
	-	42201	With 60" PLUS II <sup>™</sup> compact ball valve fittings	psi	
	-	42005	Manifold only	psi	
	-	49272*	Certified 42005 manifold		R-22/134a/404A
	-	42006 42205	Manifold with 60" PLUS II <sup>™</sup> standard fittings	psi	
EW!	-	42205	With 60" PLUS II <sup>™</sup> compact ball valve fittings Manifold only <b>A2L</b>	psi psi	R-32/454B/410A
EW!	_	42035	With 60" PLUS II <sup>™</sup> 1/4" Hoses 3-Pak RYB A2L	psi	A2L
	UPC#	UPC#	Description - °C - Red/Blue	Scale	Refrigerant
	-	41622	Manifold only	bar/psi	
	-	41852	Manifold only	kPa/psi	R-22/134a/404A
	-	41855	Manifold with 60" PLUS II <sup>™</sup> standard fittings	kPa/psi	
	-	41632	Manifold only	bar/psi	R-12/134a/413A
	_	42031 42034	Manifold only With 60" PLUS II <sup>™</sup> hose, standard fittings	psi	R-22/404A/410A
	-	41866	Manifold only	bar/psi	R600A/600/290
	41784	-	Manifold only with 5/16" fittings	MPa	R-32/410A

## SERIES 41 DELUXE MANIFOLDS °F Class 1 (1% accuracy) brass gauges



All the same features as the regular "Series 41" with 1% accuracy (Class 1) brass gauges

- Upgraded movement with phosphor bronze plates, brass gears and pinions. Dissimilar parts create less friction and last longer.
   FlutterLess<sup>™</sup> technology included
- Polished solid brass case with glass crystals
- Made in the USA

UPC#	Description	Scale	Refrigerant
44235	With 60" PLUS II™ SealRight fittings	psi	R-12/22/502
42332	Manifold only	psi	
42333	With 36" PLUS II™ compact ball valve fittings	psi	
42436	With 60" PLUS II™ compact ball valve fittings	psi	R-22/134a/ 404A
42435	With 60" PLUS II <sup>™</sup> standard fittings	psi	
45221	Retro manifold °C	psi	R-134a/404A 407C
45222	Retro manifold °F	psi	



DETECTORS AND MONITORS

. CHARGING SYSTEMS

**2. GAUGES** 

3. RECOVERY MACHINES

4. VACUUM PUMP

5. VACUUM AND CHARGING HOSES

6. HOSE ADAPTERS, VALVES & PARTS

7. WIRELESS AND Electronic Instruments

8. LEAK

NE NE

**SYSTEMS**