


**VENTILATION PRODUCTS**

**Duct Fans**

Features electrical junction box for UL and code compliant electrical connection. An efficient way to increase air circulation, keep room temperatures consistent, and lower heating and cooling costs. Metal construction, powerful no-maintenance motors and a one-use thermal fuse mean these fans will be up to the task for years. Straight forward installation into any 120V system with detailed instructions, templates, and diagrams. Available in many sizes. A great way to give slow vents a boost. Conforms to UL STD 507, Certified to CSA STD C22.2 #113



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>625-AF6</b>	Duct Fan 6" dia., 240 CFM, 37W	EA	4
<b>625-AF8</b>	Duct Fan 8" dia., 420 CFM, 37W	EA	4
<b>625-AF10</b>	Duct Fan 10" dia., 650 CFM, 35W	EA	4
<b>625-AF12</b>	Duct Fan 12" dia., 975 CFM, 65W	EA	2
<b>625-AF14</b>	Duct Fan 14" dia., 1350 CFM, 65W	EA	1

**No-Caulk Roof Flashing**

These No-Caulk Roof Flashings provide a watertight seal for vent pipes. They are available for all common pipe sizes with either a galvanized steel or thermoplastic base. Easy to install. Slides over pipe for pitch to 40° - 45. Made either of rust-proof, stamped 28 gauge galvanized steel or non-fading, non-cracking rigid black thermoplastic. Non-fading sealing collar. Approved for Type B installations. Do not use paint or petroleum-based products on plastic bases or rubber collar.



**Oatey**

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>5-11830</b>	Roof Flashing - 1/2" - 3/4" - 1"	EA	12
<b>5-11840</b>	Roof Flashing - 1-1/4" - 1-1/2"	EA	12
<b>5-11853</b>	Roof Flashing - 2"	EA	12
<b>5-11866</b>	Roof Flashing - 3"	EA	12
<b>5-11879</b>	Roof Flashing - 4"	EA	12
<b>530-11908</b>	Roof Flashing, Thermoplastic, 1-1/4" - 1-1/2"	EA	12
<b>530-11909</b>	Roof Flashing, Thermoplastic, 2"	EA	12
<b>530-11910</b>	Roof Flashing, Thermoplastic, 3"	EA	12
<b>530-11911</b>	Roof Flashing, Thermoplastic, 4"	EA	12
<b>530-11919</b>	Roof Flashing, Thermoplastic, 1-1/2" - 3"	EA	12

**Roof Louver**

Unique interior louver design, eliminating the need for a screen. The square hood has been designed for maximum air movement. Large nailing flange for easy installation. U.L. Listed.



**LESIE LOCKE**

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>6-R50A</b>	Roof Louver - Aluminum	EA	10

**Flue Caps**

PVC Flue Caps are an affordable way to protect today's high efficiency furnaces from dirt, moisture and other debris.

- Protection for high efficiency furnaces
- Universal flue cap fits 1.5", 2" and 3" PVC pipe
- Reduces draft inducer motor rust
- Helps to eliminate pressure switch service calls
- Resistant to UV radiation and oxidative degradation
- CSA approved for use in 90% AFUE heating applications



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>EC-1</b>	E cap Flue Cap	EA	12

**Smokeys**

Smoke emitter cartridges provide effective, low cost leak testing of heat exchangers, air ducts, tanks and boilers. Visual air balancing of HVAC systems. Cartridges produce clean, oil free smoke through chemical reaction. Use also for fire drills as well as the placement and testing of smoke alarms/detectors.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>14145</b>	45 second burn time, 150 cu. ft., pack of 10	PK	1
<b>14175</b>	75 second burn time, 600 cu. ft., pack of 10	PK	1
<b>14250</b>	2-1/2 minute burn time, 1,100 cu. ft., pack of 5	PK	1
<b>14340</b>	4 minute burn time, 2,500 cu. ft., pack of 5	PK	1

**Versa Cap® Flue and Hot Stack Caps**

Non clogging positive draft design, recommended for flue or hot stack installation. Clamp fitting adjustable for all standard sizes. Aluminum model. U.L. Listed.




**LESIE LOCKE**

CATALOG NO.	PIPE O.D.	DOUBLE WALL	SINGLE WALL	J-M TRANS. SITE	HEIGHT/OVERALL DIAMETER	UOM	ORDER MULTIPLE
<b>6-3050</b>	2-7/8"-5"	3 and 4	3 and 4	3 and 4	4-1/2" x 6-5/8"	EA	12
<b>6-5070</b>	4-7/8"-7"	5 and 6	5 and 6	5 and 6	4-3/4" x 9-1/2"	EA	12
<b>6-7090</b>	6-7/8"-9"	7 and 8	7 and 8	7 and 8	5-7/8" x 11-5/8"	EA	12
<b>6-9011</b>	8-7/8"-11"	9 and 10	9 and 10	9 and 10	6-1/2" x 12-3/4"	EA	6
<b>6-1200</b>	11-7/8"-14-1/2"	12	12 and 14	12	8-11/16" x 17-9/16"	EA	2

**Egg Crate Louvers - Air Return Diffusers**

White polystyrene 1/2 in. open cell grid louvers are beneficial for air return.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>650-300</b>	Egg Crate Louvers - 2' x 2' x 1/2"	EA	20
<b>650-200</b>	Egg Crate Louvers - 2' x 4' x 3/8"	EA	15
<b>650-100</b>	Egg Crate Louvers - 2' x 4' x 1/2"	EA	10