KLEIN TOOLS

Hollow-Shaft Nut Drivers

Includes core Cushion-Grip™ Nut Driver features plus:

- 3" (7.6 cm) length for most long bolt and stud applications
- 6" (15 cm) length reaches into deep recesses and fits over extra-long bolts and studs

630-11MM

1000 V

646-5/8-INS

Cat. No.	Nut Driver Sizes	Shaft Length	Insulated	Color Code	Overall Length	Cushion-Grip™ Nut Driver Sets: 631 7-Pc	647 7-Pc	65160 7-Pc	633 4-Pc	610 2-Pc	33524 9-Pc Insulated
610-1/4	1/4"	1.5" (3.8 cm)	No	Yellow	3.5" (8.9 cm)	—	—	—	—	●	—
610-5/16	5/16"	1.5" (3.8 cm)	No	Yellow	3.5" (8.9 cm)	—	—	—	—	●	—
630-3/16	3/16"	3" (7.6 cm)	No	Black	6.75" (17.2 cm)	●	—	—	—	—	—
630-1/4	1/4"	3" (7.6 cm)	No	Red	6.75" (17.2 cm)	●	—	—	●	—	—
630-5/16	5/16"	3" (7.6 cm)	No	Yellow	6.75" (17.2 cm)	●	—	—	●	—	—
630-11/32	11/32"	3" (7.6 cm)	No	Green	6.75" (17.2 cm)	●	—	—	—	—	—
630-3/8	3/8"	3" (7.6 cm)	No	Blue	6.75" (17.2 cm)	●	—	—	●	—	—
630-7/16	7/16"	3" (7.6 cm)	No	Brown	7.313" (18.6 cm)	●	—	—	—	—	—
630-1/2	1/2"	3" (7.6 cm)	No	Red	7.313" (18.6 cm)	●	—	—	—	—	—
630-9/16	9/16"	4" (10.2 cm)	No	Orange	9.375" (23.8 cm)	—	—	—	●	—	—
630-5/8	5/8"	4" (10.2 cm)	No	Yellow	9.375" (23.8 cm)	—	—	—	—	—	—
646-3/16	3/16"	6" (15.2 cm)	No	Black	9.75" (24.8 cm)	—	●	—	—	—	—
646-3/16-INS	3/16"	6" (15.2 cm)	Yes	Black	9.75" (24.8 cm)	—	—	—	—	—	●
646-1/4	1/4"	6" (15.2 cm)	No	Red	9.75" (24.8 cm)	—	●	—	—	—	—
646-1/4-INS	1/4"	6" (15.2 cm)	Yes	Red	9.75" (24.8 cm)	—	—	—	—	—	●
646-5/16	5/16"	6" (15.2 cm)	No	Yellow	9.75" (24.8 cm)	—	●	—	—	—	—
646-5/16-INS	5/16"	6" (15.2 cm)	Yes	Yellow	9.75" (24.8 cm)	—	—	—	—	—	●
646-11/32	11/32"	6" (15.2 cm)	No	Green	9.75" (24.8 cm)	—	●	—	—	—	—
646-11/32-INS	11/32"	6" (15.2 cm)	Yes	Green	9.75" (24.8 cm)	—	—	—	—	—	●
646-3/8	3/8"	6" (15.2 cm)	No	Blue	9.75" (24.8 cm)	—	●	—	—	—	—
646-3/8-INS	3/8"	6" (15.2 cm)	Yes	Blue	10.313" (26.2 cm)	—	—	—	—	—	●
646-7/16	7/16"	6" (15.2 cm)	No	Brown	10.313" (26.2 cm)	—	●	—	—	—	—
646-7/16-INS	7/16"	6" (15.2 cm)	Yes	Brown	10.313" (26.2 cm)	—	—	—	—	—	●
646-1/2	1/2"	6" (15.2 cm)	No	Red	10.313" (26.2 cm)	—	●	—	—	—	—
646-1/2-INS	1/2"	6" (15.2 cm)	Yes	Red	11.375" (28.9 cm)	—	—	—	—	—	●
646-9/16	9/16"	6" (15.2 cm)	No	Orange	11.375" (28.9 cm)	—	—	—	—	—	—
646-9/16-INS	9/16"	6" (15.2 cm)	Yes	Orange	11.375" (28.9 cm)	—	—	—	—	—	●
646-5/8	5/8"	6" (15.2 cm)	No	Yellow	11.375" (28.9 cm)	—	—	—	—	—	—
646-5/8-INS	5/8"	6" (15.2 cm)	Yes	Yellow	11.375" (28.9 cm)	—	—	—	—	—	●
Metric											
630-4MM	4 mm	3" (7.6 cm)	No	Red	6.75" (17.2 cm)	—	—	—	—	—	—
630-4.5MM	4.5 mm	3" (7.6 cm)	No	Yellow	6.75" (17.2 cm)	—	—	—	—	—	—
630-5MM	5 mm	3" (7.6 cm)	No	Black	6.75" (17.2 cm)	—	—	●	—	—	—
630-55MM	5.5 mm	3" (7.6 cm)	No	Black	6.75" (17.2 cm)	—	—	●	—	—	—
630-6MM	6 mm	3" (7.6 cm)	No	Red	6.75" (17.2 cm)	—	—	●	—	—	—
630-7MM	7 mm	3" (7.6 cm)	No	Orange	6.75" (17.2 cm)	—	—	●	—	—	—
630-8MM	8 mm	3" (7.6 cm)	No	Yellow	6.75" (17.2 cm)	—	—	●	—	—	—
630-9MM	9 mm	3" (7.6 cm)	No	Green	6.75" (17.2 cm)	—	—	●	—	—	—
630-10MM	10 mm	3" (7.6 cm)	No	Blue	6.75" (17.2 cm)	—	—	●	—	—	—
630-11MM	11 mm	3" (7.6 cm)	No	Brown	7.313" (18.6 cm)	—	—	—	—	—	—

*3/16" magnetic nut driver does not have hollow shaft.

1000 V