



## TESTERS, LEADS, CLIPS, FUSES

### Clips

The clips are alligator clips and have vinyl red and black insulators.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>5033</b>	Steel Alligator Clips for use with test probes (.075"-.080"); 1-31/32" long; jaws open 5/16" max., pack of 2 red, 2 black, 4 clips	PK	1
<b>5035</b>	Copper Alligator Clips; 1-31/32" long; jaws open 5/16" max.; crimper slotted screw connection, pack of 2 red, 2 black, 4 clips	PK	1
<b>5036</b>	Steel Test Clips; 20A, 2-7/16" long; jaws open 5/8" max.; crimper slotted screw connection, pack of 1 red, 1 black, 2 clips	PK	1

### Blade (Auto) Fuses

These fuses are used to protect circuits in the wiring harness that are usually found under the hood, in a fuse panel or supplementary panel near the battery. MAX fuses are used in domestic and import vehicles.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>ED-AT3</b>	Blade Fuse – 3 Amp – Purple, pack of 10	PK	1
<b>ED-AT5</b>	Blade Fuse – 5 Amp – Tan, pack of 10	PK	1

### Test Leads

These are replacement leads.



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>5031</b>	Low Voltage Test Leads; eight 22" long, color-coded leads with fully insulated alligator clips	EA	1
<b>5041</b>	Small Hook Type Low Voltage Test Leads; retractable hooks, 36" thermoplastic 22 gauge wire, nylon body/plunger, red/black	EA	1
<b>5042</b>	Large Hook Type Low Voltage Test Leads; retractable hooks, 36" PVC insulated 20 gauge wire, nylon body/plunger, red/black	EA	1
<b>5046</b>	Flexible Test Leads; steel alligator clips with vinyl red and black insulators; 36" 20 gauge wire; extremely flexible	EA	1

### Dual Element Fuses – 250V

Provides time delay for temporary over-current conditions and motor running protection for heating and air conditioning equipment. Eliminates unnecessary maintenance from harmless overloads.




CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
<b>ED-CR15</b>	Dual Element Fuse – 15 Amps, pack of 2	PK	1
<b>ED-CR20</b>	Dual Element Fuse – 20 Amps, pack of 2	PK	1
<b>ED-CR25</b>	Dual Element Fuse – 25 Amps, pack of 2	PK	1
<b>ED-CR30</b>	Dual Element Fuse – 30 Amps, pack of 2	PK	1
<b>ED-CR35</b>	Dual Element Fuse – 35 Amps, pack of 2	PK	1
<b>ED-CR40</b>	Dual Element Fuse – 40 Amps, pack of 2	PK	1
<b>ED-CR45</b>	Dual Element Fuse – 45 Amps, pack of 2	PK	1
<b>ED-CR50</b>	Dual Element Fuse – 50 Amps, pack of 2	PK	1
<b>ED-CR60</b>	Dual Element Fuse – 60 Amps, pack of 2	PK	1

U.L. Class RK-5, Standard for Safety 198E, Current Limiting Fuses, Interrupting Rating 200,000 Amps. rms. A.C.

## WIRE

### TFFN Stranded Hook-Up Wire\*


Packaged in handy dispenser bag. Polyvinyl chloride insulation. Wire rating: 600V, 90°C. Insulation: oil resistant nylon coating.



CATALOG NO.	COLOR	GAUGE	STRANDS	O.D.	LENGTH	UOM	ORDER MULTIPLE
<b>60331B</b>	Black, pack of 50'	18	16	.09"	48'	PK	1
<b>60331BE</b>	Blue, pack of 50'	18	16	.09"	48'	PK	1
<b>60331R</b>	Red, pack of 50'	18	16	.09"	48'	PK	1
<b>6332B</b>	Black, pack of 50'	16	26	.10"	48'	PK	1
<b>6332G</b>	Green, pack of 50'	16	26	.10"	48'	PK	1
<b>6332R</b>	Red, pack of 50'	16	26	.10"	48'	PK	1
<b>6332W</b>	White, pack of 50'	16	26	.10"	48'	PK	1

### THHN Stranded Hook-Up Wire\*

Packaged in handy dispenser bag. Polyvinyl chloride insulation. Wire rating: 600V, 90°C. Insulation: oil resistant nylon coating.



CATALOG NO.	COLOR	GAUGE	STRANDS	O.D.	LENGTH	UOM	ORDER MULTIPLE
<b>6333B</b>	Black, pack of 50'	14	19	.11"	48'	PK	1
<b>6333G</b>	Green, pack of 50'	14	19	.11"	48'	PK	1
<b>6333R</b>	Red, pack of 50'	14	19	.11"	48'	PK	1
<b>6333W</b>	White, pack of 50'	14	19	.11"	48'	PK	1
<b>6334B</b>	Black, pack of 50'	12	19	.13"	48'	PK	1
<b>6334G</b>	Green, pack of 50'	12	19	.13"	48'	PK	1
<b>6334R</b>	Red, pack of 50'	12	19	.13"	48'	PK	1
<b>6334W</b>	White, pack of 50'	12	19	.13"	48'	PK	1
<b>6335B</b>	Black, pack of 50'	10	19	.17"	48'	PK	1
<b>6335G</b>	Green, pack of 50'	10	19	.17"	48'	PK	1
<b>6335R</b>	Red, pack of 50'	10	19	.17"	48'	PK	1
<b>6335W</b>	White, pack of 50'	10	19	.17"	48'	PK	1
<b>6360B</b>	Black, pack of 50'	8	19	.22"	25'	PK	1
<b>6360R</b>	Red, pack of 50'	8	19	.22"	25'	PK	1
<b>6360W</b>	White, pack of 50'	8	19	.22"	25'	PK	1