



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 1 of 13

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

Product identifier used on the label  
: **MELTDOWN SOS®**

Other means of identification : 90124

Recommended use of the chemical and restrictions on use  
: Fuel system treatment  
No restrictions on use known.

Chemical family : Mixture.

Name, address, and telephone number  
of the supplier:

**FPPF Chemical Company, Inc.**

100 Dingens St.  
Buffalo, NY, USA 14206

Supplier's Telephone # :

**24 Hr. Emergency Tel #** : PERS: North America 1-800-633-8253; International : +1-801-629-0667  
Contract No.: 8027

Name, address, and telephone number of  
the manufacturer:

Refer to supplier

### SECTION 2. HAZARDS IDENTIFICATION

#### Classification of the chemical

Light amber liquid. Hydrocarbon-like odor

Most important hazards :Flammable liquid and vapor. May be ignited by open flames and sparks. Causes serious eye damage. Aspiration hazard. May cause respiratory irritation. May cause drowsiness or dizziness.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

#### Classification:

Flammable Liquids - Category 3

Eye Damage -Category 1

Aspiration Toxicity - Category 1

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific Target organ toxicity, repeated exposure- Category 1

#### Label elements

Hazard pictogram(s)



Signal Word

**DANGER!**

Hazard statement(s)

Flammable liquid and vapor.  
Causes serious eye damage.  
May be fatal if swallowed and enters airways.  
May cause drowsiness and dizziness.



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 2 of 13

## SAFETY DATA SHEET

### Precautionary statement(s)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.  
Ground/Bond container and receiving equipment.  
Use explosion-proof electrical and ventilating equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wear protective gloves and eye/face protection.  
Wash thoroughly after handling.  
Do not breathe mist or vapor.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.

Get medical advice/attention if you feel unwell.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire, use dry chemical, CO<sub>2</sub>, or alcohol foam to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up. Keep container tightly closed.

Dispose of in accordance with local regulations.

### Other hazards

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. May cause mild skin irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture.

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Distillates, petroleum, hydrotreated light	Distillates (petroleum), hydrotreated light	64742-47-8	Proprietary
n-propanol	n-Propyl alcohol Ethyl carbinol Hydroxypropane	71-23-8	Proprietary
Naphthalene	Naphthalin	91-20-3	Trace
Ethylbenzene	Ethylbenzol Phenylethane	100-41-4	Trace
Benzene	Phenyl hydride Coal naphtha	71-43-2	Trace
Toluene	Methylbenzene	108-88-3	Trace

The exact concentrations of the above listed chemicals are being withheld as a trade secret.



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 3 of 13

## SAFETY DATA SHEET

### SECTION 4. FIRST-AID MEASURES

#### Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration. Never give anything by mouth to a person who is unconscious or is having convulsions.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.
- Skin contact* : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 20 minutes. Immediately call a POISON CENTER or doctor/physician.

#### Most important symptoms and effects, both acute and delayed

- : Causes serious eye damage. Permanent eye damage including blindness could result. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing. May cause mild skin irritation. Symptoms may include mild redness and swelling. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Provide general supportive measures and treat symptomatically. Show this safety data sheet to the doctor in attendance.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

##### *Suitable extinguishing media*

- : Dry chemical, foam, carbon dioxide and water fog.

##### *Unsuitable extinguishing media*

- : Do not use a solid water stream as it may scatter and spread fire.

#### Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable liquid and vapor. Keep away from heat, sparks and open flames. Product may float, and be re-ignited at the water's surface. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. This product will accumulate static charge by flow, splashing or agitation. Closed containers may build up pressure when exposed to heat and flame.

#### Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquids - Category 3

#### Hazardous combustion products

- : Irritating or noxious fumes, acrid smoke, and carbon oxides.

#### Special protective equipment and precautions for firefighters

##### *Protective equipment for fire-fighters*



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 4 of 13

## SAFETY DATA SHEET

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

### *Special fire-fighting procedures*

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

### Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. Bond and ground transfer containers and equipment to avoid static accumulation. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

### Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).  
US CERCLA Reportable quantity (RQ): None.

## SECTION 7. HANDLING AND STORAGE

### Precautions for safe handling

- : Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves and eye/face protection. Do not breathe mist or vapor. Do not ingest. Avoid contact with skin, eyes and clothing. Wash hands before eating, drinking or smoking. Avoid contact with incompatible materials.

**Conditions for safe storage** : Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

**Incompatible materials** : Strong oxidizing agents ; Strong acids ; Alkali metals ; Alkaline earth metals



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 5 of 13

## SAFETY DATA SHEET

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Distillates, petroleum, hydrotreated light	200 mg/m <sup>3</sup> (as total hydrocarbon vapour)	N/Av	N/Av	N/Av
n-propanol	100 ppm	N/Av	200 ppm (500 mg/m <sup>3</sup> )	N/Av
Naphthalene	10 ppm (skin)	N/Av	10 ppm (50 mg/m <sup>3</sup> )	N/Av
Ethylbenzene	20 ppm	N/Av	100 ppm (435 mg/m <sup>3</sup> )	N/Av
Benzene	0.5 ppm (skin)	2.5 ppm (skin)	10 ppm	25 ppm (Ceiling)
Toluene	20 ppm	N/Av	200 ppm	300 ppm (Ceiling)

#### Exposure controls

##### Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

##### Respiratory protection

: If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

##### Skin protection

: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

##### Eye / face protection

: Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.

##### Other protective equipment

: Other equipment may be required depending on workplace standards. Other equipment may be required depending on workplace standards.

##### General hygiene considerations

: Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : Light amber liquid.  
**Odour** : hydrocarbon-like odor  
**Odour threshold** : N/Av  
**pH** : N/Av  
**Melting Point/Freezing point** : N/Av

##### Initial boiling point and boiling range

: Approximately 121°C / 250°F



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 6 of 13

## SAFETY DATA SHEET

Flash point : 48.9°C / 120°F  
Flashpoint (Method) : Tag closed cup  
Evaporation rate (BuAe = 1) : <1  
Flammability (solid, gas) : N/Ap  
Lower flammable limit (% by vol.) : 1.0%  
Upper flammable limit (% by vol.) : 12.0%  
Oxidizing properties : None.  
Explosive properties : N/Av  
Vapour pressure : Approximately 10  
Vapour density : >1  
Relative density / Specific gravity : 0.85  
Solubility in water : N/Av  
Other solubility(ies) : N/Av  
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution : N/Av  
Auto-ignition temperature : N/Av  
Decomposition temperature : N/Av  
Viscosity : N/Av  
Volatiles (% by weight) : N/Av  
Volatile organic Compounds (VOC's) : N/Av  
Absolute pressure of container : N/Ap  
Flame projection length : N/Ap  
Other physical/chemical comments : None reported by the manufacturer.

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : Hazardous polymerization will not occur. May be sensitive to static discharge.  
Conditions to avoid : Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials.  
Incompatible materials : Strong oxidizing agents ;Strong acids ;Alkali metals ;Alkaline earth metals  
Hazardous decomposition products : None reported. Refer also to hazardous combustion products, Section 5.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure:

Routes of entry inhalation : YES  
Routes of entry skin & eye : YES  
Routes of entry Ingestion : YES



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 7 of 13

## SAFETY DATA SHEET

### Routes of exposure skin absorption

: NO

### Potential Health Effects:

#### Signs and symptoms of short-term (acute) exposure

##### *Sign and symptoms Inhalation*

: May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

##### *Sign and symptoms ingestion*

: May cause gastrointestinal discomfort. Symptoms may include severe abdominal pain, vomiting, burns and bleeding. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

##### *Sign and symptoms skin*

: May cause mild skin irritation. Symptoms may include mild redness and swelling.

##### *Sign and symptoms eyes*

: Causes serious eye damage. Permanent eye damage including blindness could result.

#### Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Mutagenicity

: Not expected to be mutagenic in humans.

#### Carcinogenicity

: Contains material which can cause cancer. However, the concentration in this mixture is below the concentration cutoff required for classification.  
Contains :Naphthalene; Benzene;Ethylbenzene.

#### Reproductive effects & Teratogenicity

: Contains material that may cause adverse reproductive effects. However, the concentration in this mixture is below the concentration cutoff required for classification. Contains :Toluene

#### Sensitization to material

: Not expected to be a respiratory sensitizer.  
Not expected to be a skin sensitizer.

#### Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

##### Classification:

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)  
May cause drowsiness or dizziness.

#### Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

#### Synergistic materials

: None reported by the manufacturer.

#### Toxicological data

: The calculated ATE values for this mixture are:  
ATE oral =4657mg/kg  
ATE dermal =10125mg/kg  
ATE inhalation (vapours) =35.7mg/L/4H

See below for individual ingredient acute toxicity data.



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 8 of 13

## SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC<sub>50</sub>(4hr)</u> <u>inh, rat</u>	<u>LD<sub>50</sub></u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Distillates, petroleum, hydrotreated light	>6.03 mg/L (aerosol)	>5000 mg/kg	>2000 mg/kg
n-propanol	> 13 548 ppm (33.8 mg/L) (vapour) (No mortality)	1870 mg/kg	4050 mg/kg
Naphthalene	N/Av	490 mg/kg (rat) 533 mg/kg (mouse)	> 20 000 mg/kg
Ethylbenzene	4000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg
Benzene	13 700 ppm (43.8 mg/L) (vapour)	930 mg/kg	> 8240 mg/kg
Toluene	7585 ppm (28.1 mg/L)	5580 mg/kg	12 125 mg/kg

### Other important toxicological hazards

: None known or reported by the manufacturer.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

: No data is available on the product itself.  
See the following tables for individual ingredient ecotoxicity data.

### Ecotoxicity data:

<u>Ingredients</u>	<u>CAS #</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Distillates, petroleum, hydrotreated light	64742-47-8	45 mg/L (Fathead minnow)	N/Av	None.
n-propanol	71-23-8	4555 mg/L (Fathead minnow)	N/Av	None.
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	0.12 mg/L/40 days	1
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L (30 days) (QSAR)	None.
Benzene	71-43-2	5.3 mg/L (Rainbow trout) (OECD)	0.8 mg/L/32 days NOEL (OECD)	None.
Toluene	108-88-3	5.4 mg/L (pink salmon)	1.4 - 4 mg/L	None.





**MELTDOWN SOS®**

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 9 of 13

**SAFETY DATA SHEET**

<u>Ingredients</u>	CAS #	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Distillates, petroleum, hydrotreated light	64742-47-8	N/Av	N/Av	N/Av
n-propanol	71-23-8	3644 mg/L (Daphnia magna)	> 100 mg/L	None.
Naphthalene	91-20-3	3.4 mg/L (Daphnia magna)	0.22 - 0.6 mg/L	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.
Benzene	71-43-2	10 mg/L (Daphnia magna) (OECD)	N/Av	None.
Toluene	108-88-3	3.78 mg/L (Daphnia magna)	0.53 - 1 mg/L	None.

<u>Ingredients</u>	CAS #	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Distillates, petroleum, hydrotreated light	64742-47-8	N/Av	N/Av	N/Av
n-propanol	71-23-8	N/Av	N/Av	None.
Naphthalene	91-20-3	0.4 mg/L/72hr (Skeletonema costatum)	N/Av	1
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.
Benzene	71-43-2	29 mg/L/72hr (Green algae) (literature)	N/Av	None.
Toluene	108-88-3	N/Av	10 mg/L/72hr (Green algae)	None.

**Persistence and degradability**

: No data is available on the product itself.

**Bioaccumulation potential**

: No data is available on the product itself.  
See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
n-propanol	1.6	3
Distillates, petroleum, hydrotreated light	5.1-8.8	N/Av
Naphthalene	3.7	427 (Fathead minnow)
Ethylbenzene	3.15	1.1 - 1.5
Benzene	2.13	10 (Fish)
Toluene	2.65	

**Mobility in soil**

: No data is available on the product itself.

**Other Adverse Environmental effects**

: The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021





Page 10 of 13

## SAFETY DATA SHEET

### SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method.

### SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
ICAO/IATA	UN1993	Flammable liquid, n.o.s. (n-propanol)	3	III	
<b>ICAO/IATA Additional information</b>	Refer to ICAO/IATA Packing Instruction				
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (n-propanol)	3	III	
<b>IMDG Additional information</b>	Consult the IMDG regulations for exceptions.				
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (n-propanol )	3	III	
<b>49CFR/DOT Additional information</b>	This material may be reclassified as a 'Combustible liquid', when shipping by ground within the United States only. Combustible liquids may be shipped as non-hazardous material when shipped in non-bulk containers (450 L / 119 Gallons or less). Refer to 49 CFR Section 173.150. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (n-propanol )	3	III	
<b>TDG Additional information</b>	May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass.				

- Special precautions for user** : Keep away from heat, sparks and open flame - No smoking.
- Environmental hazards** : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
 : Not available.

### SECTION 15 - REGULATORY INFORMATION

**US Federal Information:**

Components listed below are present on the following U.S. Federal chemical lists:



**MELTDOWN SOS®**

SDS Revision Date (mm/dd/yyyy): 04/11/2021

**SAFETY DATA SHEET**

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity (RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Distillates, petroleum, hydrotreated light	64742-47-8	Yes	N/Ap	N/Av	No	N/Ap
n-propanol	71-23-8	Yes	None.	None.	No	N/Ap
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	None.	Yes	Yes
Ethylbenzene	100-41-4	Yes	1000 lb/ 454 kg	None.	Yes	Yes
Benzene	71-43-2	Yes	10 lb / 4.54 kg	None.	Yes	Yes
Toluene	108-88-3	Yes	1000 lb/ 454 kg	None.	No	No

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable; Eye Damage ;Specific target organ toxicity, single exposure ; Aspiration hazard.Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

**US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Distillates, petroleum, hydrotreated light	64742-47-8	No	N/Ap	No	No	No	No	No	No
n-propanol	71-23-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Naphthalene	91-20-3	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes
Benzene	71-43-2	Yes	Cancer; male reproductive toxicity; Developmental	Yes	Yes	Yes	Yes	Yes	Yes
Toluene	108-88-3	Yes	Developmental	No	No	Yes	No	No	Yes

**Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

**International Information:**

Components listed below are present on the following International Inventory list:



MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 12 of 13

## SAFETY DATA SHEET

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Distillates, petroleum, hydrotreated light	64742-47-8	265-149-8	Present	Present	(9)-1700	KE-12550	Present	No information available.
n-propanol	71-23-8	200-746-9	Present	Present	(2)-207	KE-29362	Present	HSR001215
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151
Benzene	71-43-2	200-753-7	Present	Present	(3)-1	KE-02150	Present	HSR001038
Toluene	108-88-3	203-625-9	Present	Present	(3)-2	KE-33936	Present	HSR001227

### SECTION 16. OTHER INFORMATION

#### Legend

: ACGIH: American Conference of Governmental Industrial Hygienists  
ATE: Acute Toxicity Estimate  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
CNS: Central Nervous System  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EC50: Effective Concentration 50%  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
IMDG: International Maritime Dangerous Goods  
Inh: Inhalation  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
MSHA: Mine Safety and Health Administration  
N/Av: Not Applicable  
N/Av: Not Available  
NIOSH: National Institute of Occupational Safety and Health  
NTP: National Toxicology Program  
NOEC: No observable effect concentration  
OSHA: Occupational Safety and Health Administration  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System



---

MELTDOWN SOS®

SDS Revision Date (mm/dd/yyyy): 04/11/2021

Page 13 of 13

## SAFETY DATA SHEET

**References** : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices  
2. ECHA - European Chemical Agency  
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, (Chempendium, HSDB and RTECs).  
4. Safety Data Sheets from manufacturer.  
5. US EPA Title III List of Lists  
6. California Proposition 65 List  
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

**Preparation Date (mm/dd/yyyy)**

: 04/22/2020

**Reviewed Date SDS (dd/mm/yyyy)**

: 11/04/2021

**Revision No.**

: 2

**Revision Information**

: All sections modified.

**Other special considerations for handling**

: Provide adequate information, instruction and training for operators.

**Prepared for:**

FPPF Chemical Company, Inc.  
100 Dingens St.  
Buffalo, NY, USA 14206  
Telephone: 1-800-735-3773  
Please direct all enquiries to FPPF Chemical Company

### DISCLAIMER

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of FPPF Chemical Company, Inc.

**END OF DOCUMENT**