



# RESIDENTIAL/COMMERCIAL First Stage Regulators Type 984HP (compact)

INSTALLATION  
INSTRUCTIONS

RV AND OUTDOOR  
COOKING REGULATORS

AUTOGAS  
EQUIPMENT

FILLING  
HEADS

BULK STORAGE AND  
TRUCK EQUIPMENT

DOT/ASME  
CONTAINER VALVES

REGULATORS



984HP-04



984HP-05

### Product description

The first stage regulator reduces the inlet pressure, coming from the container, to a medium level inlet pressure for a second stage regulator. Therefore Type 984 HP regulators are designed for Type A or Type C installations found in the Installations section.

They have to be used outdoors in correct mounting position with vent-hole turned downwards. In their standard version the Type 984 HP regulators are delivered with vent-hole turned in line with the outlet fitting.

### Technical Specifications

**Body And Cover:** Aluminium

**Diaphragm:** Reinforced

**Supplying Pressure:** 25-250 PSIG

**Cover Screws:** Stainless Steel

**Gas Type:** Propane

**Setting Point:** inlet Pressure 100 PSIG, 140,000 BTU, Outlet Pressure 10 PSIG

**Provided Flows:** Flow Based On 25 PSIG Inlet Pressure and 20% Drop (In accordance with UL 144)

Type 984HP - L 4.881 x W 4.33 x H 3.917" Weight: 31.375 oz

Type (Part No.)	Capacities in BTU/hr propane	Inlet connection, inches	Outlet connection, inches	Outlet adjustment range, PSIG	Outlet pressure setting, PSIG
984HP - 04 (98.1.490.0004)	1,000,000	1/4" NPT	1/2" NPT	No adjustment	10
984HP - 05 (98.1.490.0005)	1,000,000	POL			
984HP - 06 <sup>1</sup> (98.1.490.0006)	1,000,000	1/4" NPT			

<sup>1</sup> Vent-hole opposite the gauge taps