



Kosan+ Integral Two-Stage Residential Regulators



Cavagna 10 Year Warranty.
Recommended replacement life is 25 Years.



998TW-14



998TW-11

Integral 2-Stage Regulator Technical Specifications:
 Body and cover: aluminum
 Diaphragm: reinforced
 Supplying pressure: 25-250 PSIG
 Cover screws: stainless steel
 Inlet fitting screws: stainless steel
 Gas type: propane
 Setting point: 1,400,000 Btu, outlet pressure: 11 WC
 Provided flows: flow based on 10 PSI (0.69 bar) inlet pressure and 20% drop (in accordance with UL 144 standard).

The integral 2-stage regulator uses two regulators in one body to regulate the inlet pressure of the gas from the tank or cylinder directly to the inlet pressure of the appliance. The 988TW regulator is designed for Type B outside installations. The correct mounting position is with the vent angled down. The standard 988TW regulator has the vent-hole facing in line with the outlet fitting.

Kosan+ Integral Two-Stage Residential Regulators

Part No.	Capacity BTU/HR	Inlet Connection	Outlet Connection	Outlet Adjustment Range	Outlet Pressure Setting
988TW-15	750,000	1/4" FNPT	1/2" FNPT	9-13 WC	11 WC
988TW-16*		FPOL			
988TW-17			FPOL		
988TW-18*					
998TW-11	1,400,000	1/4" FNPT	3/4" FNPT	9-13 WC	11WC
998TW-12*		FPOL			
998TW-13			FPOL		
998TW-14*					

* Vent opposite test taps



Kosan+ Integral Two-Stage 2-PSI Residential Regulators



998TW-23



Part No.	Capacity BTU/HR	Inlet Connection	Outlet Connection	Outlet Adjustment Range	Outlet Pressure Setting
998TW-23	1,400,000	1/4" FNPT	3/4" FNPT	1-2.2 PSI	2 PSI
988TW-64	500,000	FPOL	1/2" FNPT	1 to 2.2 PSIG	2 PSIG

Toledo
800 537 7518

Bowling Green
800 448 9504

Indianapolis
800 662 3252

Kansas City
800 821 3878

Minneapolis
800 328 6291