

Inverter Driven Heat Pump

7,000 BTU Wall Mount Type

Job Name _____
 Location _____
 Engineer _____
 Submitted To _____
 Submitted By _____
 Reference _____

Date _____
 Approval _____
 Construction _____
 Unit No _____
 Drawing No _____

PRODUCT FEATURES

- Wireless Remote Controller Included
- Minimum Heat Mode
- Automatic Airflow Adjustment
- Auto/Cool/Dry/Fan/Heat/modes
- Weekly & 24 Hr Timer
- Powerful & Economy Mode
- Auto Changeover
- Cold Air Prevention



MODEL NUMBERS

Indoor Unit	ASUH07LPAS
Nominal Capacity	7,000

LINESET REQUIREMENTS

Connection Method		Flare
Liquid	in (mm)	Ø1/4 (Ø6.35)
Gas		Ø3/8 (Ø9.52)
Drain hose	Material	PP+HDPE
	in	Ø17/32 (I.D.), Ø19/32 to 21/32 (O.D.)
	mm	Ø13.8 (I.D.), Ø15.0 to 16.8 (O.D.)

INDOOR DIMENSIONS & WEIGHT

Net (H x W x D)	in	10-5/8 x 32-13/16 x 8-3/4
	mm	270 x 834 x 222
Gross (H x W x D)	in	10-7/8 x 36 x 13-1/16
	mm	277 x 914 x 332
Net Weight	lb (kg)	21 (9.5)
Gross Weight		26 (12.0)

ELECTRICAL SPECIFICATIONS

Voltage/Frequency/Phase		208/230 V ~ 60 Hz
Voltage Range		187-264 V
Running Current	A	0.18
Input Power	W	18

SOUND PRESSURE

Indoor Unit	Cooling	High	dB (A)	38
		Medium		33
		Low		29
		Quiet		21
	Heating	High	dB (A)	41
		Medium		35
		Low		31
		Quiet		22

FAN DATA

Airflow Rate	Cooling	High	CFM (m3/h)	383 (650)
		Medium		318 (540)
		Low		253 (430)
		Quiet		188 (320)
	Heating	High	CFM (m3/h)	424 (720)
		Medium		341 (580)
		Low		271 (460)
		Quiet		194 (330)

Warranty Information



7 Year Compressor, 5 Year Parts out-of-the-box Warranty



10 Year Compressor, 10 Year Parts Warranty when registered within 60 days of installation in a residence



12 Year Compressor, 12 Year Parts Warranty when registered within 60 days of installation in a residence, and installed by a Fujitsu Elite contractor

ENCLOSURE

Enclosure	Material	Polystyrene
	Color	White

ACCESSORIES

UTY-RNRUZ Series	Wired Remote Controller
UTY-RSRY	Simple Remote Controller
UTY-RHRY	Simple Remote Controller
UTY-TWRXZ2*	Communication Kit
UTY-TFSXF1	Wireless LAN Interface
UTY-TTRXZ1	24V Thermostat Interface
UTY-VMSX	MODBUS Converter
FJ-AC-BAC-1L	BACnet Gateway
UTY-XWZX	External Connect Kit

* Required to connect wired remote controller to indoor unit.



Effective Date: 2/9/2022

Version ASUH07LPAS -2022A


Due to continuous product improvements, specifications are subject to change without notice. Please log in to the Fujitsu Portal for the most up-to-date documentation <https://connect.fujitsugeneral.com>

Inverter Driven Heat Pump

7,000 BTU Wall Mount Type

DIMENSIONS

Units: In. (mm)



The Fujitsu logo is a worldwide trademark of Fujitsu General Limited. The Halcyon logo and name is a worldwide trademark of Fujitsu General Limited and is a registered trademark in Japan, the USA and other countries or areas. Copyright 2022 Fujitsu General America, Inc. Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Note: Specifications are based on the following conditions:
 Cooling: Indoor temperature of 80°F (26.7°C) DB/67°F (19.4°C) WB, and outdoor temperature of 95°F (35°C) DB/75°F (23.9°C) WB. Heating: Indoor temperature of 70°F (21.1°C) DB/60°F (15.6°C) WB, and outdoor temperature of 47°F (8.3°C) DB/43°F (6.1°C) WB. Pipe length: 25ft. (7.5m), Height difference: 0ft. (0m) (Outdoor unit - indoor unit).