

Submittal Data: System 36RCLX AUU36RCLX & AOU36RLX



Job Name: _____ Location: _____

Purchaser: _____

Engineer: _____

Submitted To: _____ For: Reference Approval Construction

Submitted By: _____

Unit Designation: _____ Schedule No. _____ Model No.: _____

Capacities:

Cooling	34,100/36,000 BTU/h
Outdoor Design Temperature <i>F^o</i> DB/WB	95/75
Heating	38,200/42,700 BTU/h
Outdoor Design Temperature <i>F^o</i> DB/WB	47/43
SEER	14.0
EER <i>Clg/Htg</i>	8.1/9.7

Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L</i>	48/45/41
Noise Level Heating <i>db (A) - H/ M/ L</i>	48/45/31
Weight	82 lbs.

Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	30A
Min. Ampacity	23A
Running Current <i>Cooling</i>	18.3/18.8A
Running Current <i>Heating</i>	16.2/18.8A
Weight	141 lbs.

Refrigerant Piping:

Max Ht. Difference	98/30 ft.
Max Total or Combined Length	165 ft. each
Discharge Vapor Line (O.D.)	3/8 in.
Suction (O.D.)	5/8 in.

Standard Features:

- ◆ Six year compressor warranty
- ◆ Two year parts warranty
- ◆ Weekly timer
- ◆ Auto Louver: Up/Down
- ◆ Energy saver
- ◆ Pump Down Operation
- ◆ Slender fit
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ Auto Mode
- ◆ High Ceiling Mode
- ◆ Branch Duct Capable
- ◆ Full Function Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Quiet Mode
- ◆ Cold Prevention

Notes:

OUTLINE AND DIMENSIONS

