

TRIPLE AQUASTATS

Honeywell

New and Remanufactured Aquastats

Immersion type controllers that combine high limit protection with low limit and circulator control in forced hydronic heating systems, including domestic hot water.

FEATURES:

- Provides multi zone control by using a separate circulator and relay for each zone.
- Includes diaphragm power head and Micro-Switch™ assembly that respond to temperature changes in boiler water
- Mounts directly to boiler.
- Requires a 24 VAC thermostat with heat anticipator set at 0.2 A.



Honeywell

4

HYDRONICS

SPECIFICATIONS		ELECTRICAL RATINGS	
Frequency:	60 Hz	Burner @ 120VAC:	7.4 FLA, 44.4 LRA
Connections:	Quick connect/screws	Burner @ 240VAC:	3.7 FLA, 22.7 LRA
Mount:	Vertical	Circulator @ 120 VAC:	44.4 FLA, 7.4 LRA
Switch Action:	SPST high and low limit	Circulator @ 240 VAC:	3.7 FLA, 22.7 LRA
Low Limit Diff:	10 - 25°F adj.		
High Limit Diff.:	10°F fixed		
Low Limit Range:	110 - 220°F		
High Limit Range:	130 - 240°F		
Dimensions:	6-1/8" H x 4-5/16" W x 3-1/8" D		

Volts	Insulation Depth	Includes	Mfr#	Item#	Reman#
120 VAC	3"	---	L8124A		C317R
Millivolt	3"	---	L8124B		C317-1R
120 VAC	3"	3 insertion well	L8124A1015	C317-2B	C317-2R
120 VAC	3"	---	L8124C		C317-3R
24/120 VAC	3"	---	L8124E		C317-4R
120 VAC	1-1/2"	Universal element and mounting, heat conductive compound, less well.	L8124C1003	C317-5	C317-5R
120 VAC	3"	---	L8124G		C317-6R
120 VAC	1-1/2"	Universal element and mounting, heat conductive compound, less well. Plus, large transformer and extra power to low voltage zone valves.	L8124E1016	C317-7	C317-7R
120 VAC	3"	Same as L8124E1016 above	L8124G1020	C317-8	C317-8R
Millivolt	3"	---	L8124B		C317-9R
120 VAC	3"	---	L8124A		C317-10R
24/120 VAC	3"	Same as L8124E1016 above	L8124L1011	C317-11	C317-11R
120 VAC	3"	Molex® plug for use with vend damper, includes heat conductive compound.		L8148E1265	

NOTE: Remanufactured products available only on exchange for similar defective units.