

S106 Series Time Delay Relays

- SPST or SPDT
- Delay on/ off timing



PART NO.	A-1®		TIME DELAY ON (seconds)	TIME DELAY OFF (seconds)
	PART NO.	SWITCH ACTION		
S1061A4575C	FF582	SPST	30 to 50	60 to 90
S1061A5040C	FF583	SPST	45 to 55	30 to 50
S1061A40100C	FF584	SPST	35 to 45	80 to 110
S1061A5560C	FF585	SPST	50 to 60	45 to 75
S1061B6545C	FF586	SPDT	60 to 70	45 to 75

F47 & F214 Series Fan Controls


- Adjustable Temperature Dial



PART NO.	A-1®		WIDTH (inches)	LENGTH (inches)	FAN OFF TEMP. (°F)	FAN DIFFERENTIAL (°F)
	PART NO.	SWITCH ACTION				
F473TD12025C	FF564	SPST	7/16"	3"	90 to 120	25 to 50
F477TD12025C	FF565	SPST	7/16"	7"	90 to 120	25 to 50
F21412A14025C	FF562	SPST	1-1/16"	3"	60 to 140	25 to 50
F21413A14025C	FF563	SPST	1-1/16"	7"	60 to 140	25 to 50

L59 Series Limit Controls

- SPDT Switch
- User Temperature Adjustment



PART NO.	A-1®		FAN OFF TEMP.	FIXED DIFFERENTIAL (°F)
	PART NO.	LENGTH (inches)		
L593BA	FF568	3"	120 to 250	30
L597BA	FF569	7"	120 to 250	30

FA47TS Series Fan Controls w/ Time Start Fan Control

- Built in "Heat Assist" Time Delay
- Adjustable Fan OFF Temperature



PART NO.	A-1®		FAN OFF TEMP. (°F)	FAN DIFFERENTIAL (°F)	TIME DELAY @ 24 VAC (sec.)
	PART NO.	LENGTH (inches)			
FA47TS3110	FF566	3"	80 to 110	60 (Fixed)	25 to 60
FA47TS7110	FF567	7"	80 to 110	60 (Fixed)	25 to 60

FAL Series Universal Fan and Limit Controls

- Adjustable fan "OFF" setting
- Adjustable fan differential setting
- Adjustable Limit Temperature



PART NO.	A-1®		FAN OFF TEMP. (°F)	FAN DIFFERENTIAL (°F)	LIMIT TEMP. (°F)	LIMIT DIFFERENTIAL (°F)
	PART NO.	LENGTH (inches)				
FAL3C05TD120A	FF558	3"	90 to 120	25 to 50	150 to 250	30
FAL7C05TD120A	FF559	7"	90 to 120	25 to 50	150 to 250	30
FAL7C20BT120AB	FF594	7"	90 to 120	25 to 50	150 to 250	30

FALTS Series Fan and Limit Controls w/ Time Delay

- SPST Switch
- Adjustable Limit Temperature
- Pilot Duty: 40 VA @ 30 VAC & 120 VAC



PART NO.	A-1®		FAN OFF TEMP. (°F)	LIMIT TEMP. (°F)	LIMIT DIFFERENTIAL (°F)
	PART NO.	LENGTH (inches)			
FALTS57C05T120A	FF560	7"	90 to 120	150 to 250	30
FALTS57C65T120A	FF561	7" w/ shield	90 to 120	150 to 250	30
FALTS57C13BT120A	FF591	7" SPDT	90 to 120	150 to 250	30

PR Series Pilot Reigniters

- Prevents Pilot Flames From Extinguishing

PART NO	A1 PART NO	DESCRIPTION
PR24120	FF541	24/120 VAC Hardware Kit , Spark cable
PR2436W	FF543	24 VAC Hardware Kit, Spark Cable, & PR-24 Module
PR2412036W	FF536	24/120 VAC Hardware Kit, Spark Cable & Module



BC7070 (F7070) Blower Control

- Increase Heating Efficiency By Delaying The ON and OFF Cycle of the blower fan.
- Control Voltage: 24 VAC.
- Relay Contacts: SPST.
- Blower On Time: 0 – 240 Seconds Adjustable.
- Blower Off Time: 0 – 240 Seconds Adjustable



CIVA5 (FF534) Brown Out Delay Timer

- Short Cycle & Brown Out Protection For Compressors.
- Interlock Time: 5 minutes.
- Under Voltage Protection: Adjustable 16 – 22 VAC.
- Reset Time: 30 Milliseconds.



AFC01T110204 (FF535) Attic Fan Control

- Adjustable Fan OFF Temperature: 60°F to 110°F
- Firestat circuit for safety shut off
- SPST



For further information refer to Product Sheet F438