



TESTERS, LEADS, CLIPS, FUSES

Clips

The clips are alligator clips and have vinyl red and black insulators.



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-------------|--|-----|----------------|
| 5033 | Steel Alligator Clips for use with test probes (.075"-.080"); 1-31/32" long; jaws open 5/16" max., pack of 2 red, 2 black, 4 clips | PK | 1 |
| 5035 | Copper Alligator Clips; 1-31/32" long; jaws open 5/16" max.; crimper slotted screw connection, pack of 2 red, 2 black, 4 clips | PK | 1 |
| 5036 | Steel Test Clips; 20A, 2-7/16" long; jaws open 5/8" max.; crimper slotted screw connection, pack of 1 red, 1 black, 2 clips | PK | 1 |

Blade (Auto) Fuses

These fuses are used to protect circuits in the wiring harness that are usually found under the hood, in a fuse panel or supplementary panel near the battery. MAX fuses are used in domestic and import vehicles.



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|---------------|---|-----|----------------|
| ED-AT3 | Blade Fuse – 3 Amp – Purple, pack of 10 | PK | 1 |
| ED-AT5 | Blade Fuse – 5 Amp – Tan, pack of 10 | PK | 1 |

Test Leads

These are replacement leads.



| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|-------------|---|-----|----------------|
| 5031 | Low Voltage Test Leads; eight 22" long, color-coded leads with fully insulated alligator clips | EA | 1 |
| 5041 | Small Hook Type Low Voltage Test Leads; retractable hooks, 36" thermoplastic 22 gauge wire, nylon body/plunger, red/black | EA | 1 |
| 5042 | Large Hook Type Low Voltage Test Leads; retractable hooks, 36" PVC insulated 20 gauge wire, nylon body/plunger, red/black | EA | 1 |
| 5046 | Flexible Test Leads; steel alligator clips with vinyl red and black insulators; 36" 20 gauge wire; extremely flexible | EA | 1 |

Dual Element Fuses – 250V

Provides time delay for temporary over-current conditions and motor running protection for heating and air conditioning equipment. Eliminates unnecessary maintenance from harmless overloads.




| CATALOG NO. | DESCRIPTION | UOM | ORDER MULTIPLE |
|----------------|--|-----|----------------|
| ED-CR15 | Dual Element Fuse – 15 Amps, pack of 2 | PK | 1 |
| ED-CR20 | Dual Element Fuse – 20 Amps, pack of 2 | PK | 1 |
| ED-CR25 | Dual Element Fuse – 25 Amps, pack of 2 | PK | 1 |
| ED-CR30 | Dual Element Fuse – 30 Amps, pack of 2 | PK | 1 |
| ED-CR35 | Dual Element Fuse – 35 Amps, pack of 2 | PK | 1 |
| ED-CR40 | Dual Element Fuse – 40 Amps, pack of 2 | PK | 1 |
| ED-CR45 | Dual Element Fuse – 45 Amps, pack of 2 | PK | 1 |
| ED-CR50 | Dual Element Fuse – 50 Amps, pack of 2 | PK | 1 |
| ED-CR60 | Dual Element Fuse – 60 Amps, pack of 2 | PK | 1 |

U.L. Class RK-5, Standard for Safety 198E, Current Limiting Fuses, Interrupting Rating 200,000 Amps. rms. A.C.

WIRE

TFFN Stranded Hook-Up Wire*


Packaged in handy dispenser bag. Polyvinyl chloride insulation. Wire rating: 600V, 90°C. Insulation: oil resistant nylon coating.



| CATALOG NO. | COLOR | GAUGE | STRANDS | O.D. | LENGTH | UOM | ORDER MULTIPLE |
|----------------|--------------------|-------|---------|------|--------|-----|----------------|
| 60331B | Black, pack of 50' | 18 | 16 | .09" | 48' | PK | 1 |
| 60331BE | Blue, pack of 50' | 18 | 16 | .09" | 48' | PK | 1 |
| 60331R | Red, pack of 50' | 18 | 16 | .09" | 48' | PK | 1 |
| 6332B | Black, pack of 50' | 16 | 26 | .10" | 48' | PK | 1 |
| 6332G | Green, pack of 50' | 16 | 26 | .10" | 48' | PK | 1 |
| 6332R | Red, pack of 50' | 16 | 26 | .10" | 48' | PK | 1 |
| 6332W | White, pack of 50' | 16 | 26 | .10" | 48' | PK | 1 |

THHN Stranded Hook-Up Wire*

Packaged in handy dispenser bag. Polyvinyl chloride insulation. Wire rating: 600V, 90°C. Insulation: oil resistant nylon coating.



| CATALOG NO. | COLOR | GAUGE | STRANDS | O.D. | LENGTH | UOM | ORDER MULTIPLE |
|--------------|--------------------|-------|---------|------|--------|-----|----------------|
| 6333B | Black, pack of 50' | 14 | 19 | .11" | 48' | PK | 1 |
| 6333G | Green, pack of 50' | 14 | 19 | .11" | 48' | PK | 1 |
| 6333R | Red, pack of 50' | 14 | 19 | .11" | 48' | PK | 1 |
| 6333W | White, pack of 50' | 14 | 19 | .11" | 48' | PK | 1 |
| 6334B | Black, pack of 50' | 12 | 19 | .13" | 48' | PK | 1 |
| 6334G | Green, pack of 50' | 12 | 19 | .13" | 48' | PK | 1 |
| 6334R | Red, pack of 50' | 12 | 19 | .13" | 48' | PK | 1 |
| 6334W | White, pack of 50' | 12 | 19 | .13" | 48' | PK | 1 |
| 6335B | Black, pack of 50' | 10 | 19 | .17" | 48' | PK | 1 |
| 6335G | Green, pack of 50' | 10 | 19 | .17" | 48' | PK | 1 |
| 6335R | Red, pack of 50' | 10 | 19 | .17" | 48' | PK | 1 |
| 6335W | White, pack of 50' | 10 | 19 | .17" | 48' | PK | 1 |
| 6360B | Black, pack of 50' | 8 | 19 | .22" | 25' | PK | 1 |
| 6360R | Red, pack of 50' | 8 | 19 | .22" | 25' | PK | 1 |
| 6360W | White, pack of 50' | 8 | 19 | .22" | 25' | PK | 1 |