







PLEASE USE THE FOLLOWING ILLUSTRATIONS TO DIFFERENTIATE WHICH LINK IS REQUIRED

FIRST CHOOSE LINK TYPE, THEN SELECT TEMPERATURE

 <p>2.60in.</p> <p>Type A FL-A 165°F & 212°F ONLY</p> <p>Not Used Anymore</p>	 <p>1.50in.</p> <p>Type B No Hooks FL-B-NH CRD50-55 4X-6X ALL BOOTS</p>	 <p>3.00in.</p> <p>Type B Short Hooks FL-B-SH THINLINE SERIES</p>	 <p>3.50in.</p> <p>Type B Long Hooks FL-B-LH 75 SERIES CURTAIN DAMPERS (4.25 IN)</p>	 <p>4.00in.</p> <p>Type C 165°F & 212°F ONLY</p>	 <p>1.60in.</p> <p>Type E FL-E FSD AND FD111 165°F ONLY</p>
--	---	---	--	---	--

TYPE B FUSIBLE LINKS COME IN THE FOLLOWING TEMPERATURES:

- | | |
|--------------------------------|--------------------------------|
| <input type="checkbox"/> 135°F | <input type="checkbox"/> 285°F |
| <input type="checkbox"/> 165°F | <input type="checkbox"/> 375°F |
| <input type="checkbox"/> 212°F | <input type="checkbox"/> 386°F |