

GAS VALVES

White-Rodgers


Redundant Gas Valves

PROVEN PILOT APPLICATIONS - HOT SURFACE IGNITION - DIRECT SPARK

This combination gas manifold is a compact, multi-function valves designed for use with all types of intermittent ignition systems such as cycle pilot, proven pilot, direct spark ignition, and hot surface ignition.

FEATURES:

- Compact size.
- All valve adjustments and system interface wiring panel are located on top of the control for simplified servicing.
- Poppet style manual valve capable of withstanding high pressures.
- Conical inlet and outlet screen protect against pipe damage.
- Keyed wiring.
- Direct-acting solenoid valve with high sealing force.
- Controlled gasket clinch between casting to withstand high inlet pressures.
- Tamper-resistant screws.
- May be mounted horizontally or vertically, 90° from horizontal.
- Valves have pilot filter, adjustable pilot pressure and manual shut-off valve.



WHITE-RODGERS


| | |
|-----------------------------|-----------------------------|
| Electrical Rating: | 24 vac, 0.54 amps, 50/60 Hz |
| Ambient Temp.: | -40 - 175°F |
| Regulator Setting: | 3.5" WC |
| Max. Inlet Pressure: | 1/2 psi (14" WC) |
| Type Gas: | Natural |

| Inlet Size | Outlet Size | Capacity AGA Standard | Total Reg. Capacity | Electrical Conn. | Mfr# | Item# |
|------------|-------------|-----------------------|---------------------|------------------------|------------|-----------|
| 1/2" fpt | 3/4" fpt | 140,000 | 210,000 | 3 spade terminals 1/4" | 36E36-304* | 36H32-304 |

White-Rodgers

3600 Combination Gas Manifold Valve Accessories

| Description | Use with | Application | Mfr# | Item# |
|-------------------|--|-------------|----------|---------|
| Resistor assembly | 36C Cycle-Pilot gas valves with pressure switch 3098 plug-in mercury elements with 5059 pilot relite control | Nat. gas | F67-0918 | G567-98 |



WHITE-RODGERS

6
GAS HEATING