



7701GSO

SERIES 7701G • GAS BALL VALVE • ONE-PIECE BODY • SUREOFF HANDLE FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.	
STYLE 7701GSO – SAFETY HANDLE						
210-522RP	3/8"	FPT x FPT	-	20	0.36	<ul style="list-style-type: none"> • 200 PSI • -20°F - 300°F temperature range • SureOff tamper-resistant handle • Quarter, push-to-turn operation prevents unintentional opening of valve • Coated aluminum handle for corrosion and solvent resistance • Multi-directional flow • One-piece body for leak resistance and long valve life
210-523HC	1/2"	FPT x FPT	-	30	0.39	
210-524HC	3/4"	FPT x FPT	-	20	0.63	



- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1



7701G

SERIES 7701G • GAS BALL VALVE • ONE-PIECE BODY FORGED BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.	
STYLE 7701G – LEVER HANDLE						
110-522	3/8"	FPT x FPT	10	100	0.31	<ul style="list-style-type: none"> • 200 PSI • -20°F - 300°F temperature range • Quarter-turn lever handle for positive on/off operation • Coated aluminum handle for corrosion and solvent resistance • Multi-directional flow • One-piece body for leak resistance and long valve life
110-523	1/2"	FPT x FPT	10	100	0.39	
110-524	3/4"	FPT x FPT	10	100	0.58	

- Chrome-plated brass ball
- CSA - ANSI Z21.15 (1/2 PSIG)
- ANSI/ASME B16.44 (5G)
- UL listed
- Threaded ends comply with ANSI B1.20.1

