




# Hoses

Uniweld flexible Oxyfuel Hoses are color coded, have 8-sided crimp ferrules and are capable of withstanding high working pressures for a reliable long service life.

Reference Information: "A" = 3/8" - 24 "B" = 9/16" - 18



Hose Spring (Part#SHLP) may be added to Acetylene or LP gas hoses by adding an (S) for one spring or (SS) for two springs (one @ each end) to the hose Part#. Example: H12S, H12SS, HLP14BS, HLP14BSS

### Acetylene Single Hose

3/16" I.D., Max. W.P. 200 psi

	Part#	UPC#	Length	Connection
Acetylene Single Hose	H11	43500	6 ft.	"A"
	H11B	43501	6 ft.	"B"
	H12	43502	12 ft.	"A"
	H12B	43503	12 ft.	"B"
	H13	43504	25 ft.	"A"
	H13B	43505	25 ft.	"B"

\*\*"AB" - "A" fitted one end, "B" fitted opposite end

### LP Gas Single Hose

3/16" I.D., Max. W.P. 125 psi

	Part#	UPC#	Length	Connection
LP Gas Single Hose	HLP10	43530	3 ft.	"A"
	HLP10B	43531	3 ft.	"B"
	HLP11	43533	6 ft.	"A"
	HLP11B	43534	6 ft.	"B"
	HLP13	43537	25 ft.	"A"
	HLP13B	43538	25 ft.	"B"
	HLP14	43541	12 ft.	"A"
	HLP14B	43542	12 ft.	"B"

### Oxyacetylene Twin Hose

3/16" I.D., Max. W.P. 200 psi

	Part#	UPC#	Length	Connection
Oxyacet. Twin Hose	H32A	43510	12 ft.	"A"
	H32B	43512	12 ft.	"B"
	H32AB	43511	12 ft.	"AB**"
	H33A	43513	25 ft.	"A"
	H33B	43515	25 ft.	"B"
	H33AB	43514	25 ft.	"AB**"
	H34A	43516	50 ft.	"A"
	H34B	43517	50 ft.	"B"

\*\*"AB" - "A" fitted one end, "B" fitted opposite end

### Oxy/LP Gas Grade "T" Twin Hose

3/16" I.D., Max. W.P. 200 psi

	Part#	UPC#	Length	Connection
Oxy/LP Grade "T" Twin Hose	H32AT	43560	12 ft.	"A"
	H32BT	43561	12 ft.	"B"
	H32ABT	43562	12 ft.	"AB**"

\*\*"AB" - "A" fitted one end, "B" fitted opposite end

