


DIRECT REPLACEMENT IGNITERS

SKIT03033

Replaces Trane® KIT03033



- Steady current: 4.25 Amps @ 115 VAC.
- Max. Current: 5 Amps @ 132VAC.
- Time to Temp (1800°F): < 17 seconds

SPLT3400

Replaces Lochinvar® PLT3400



- Steady Current: 4.25 Amps @ 115 VAC.
- Max. Current: 5 Amps @ 132 VAC.
- Time to Temp (1800°F): < 17 seconds

S0230K00000S

Replaces Goodman® 0230K00000S



- Steady Current: 4.25 Amps @ 115 VAC.
- Max. Current: 5 Amps @ 132 VAC.
- Time to Temp (1800°F): < 17 seconds

FLAT SILICON CARBIDE IGNITERS



IG4000 Super Kit

5 Brackets & Hardware
Replaces:
41-402, 41-403, 41-404,
41-405, 41-407, 41-408,
41-409, 41-410,
41-412, 41-414, 41-1090,
41-238, 41-242




IG401

Replaces: 41-401




IG402K Kit

Replaces:
41-402, 41-408,
41-410, 41-411



IG403K Kit

Replaces:
41-403, 41-404,
41-407, 41-409



IG404

Replaces: 41-404



IG405

Replaces: 41-405




IG406

Replaces: 41-406



IG407

Replaces: 41-407



IG408

Replaces: 41-408




IG409

Replaces: 41-409



IG410

Replaces: 41-410



IG411

Replaces: 41-411



IG412

Replaces: 41-412



IG414

Replaces: 41-414



IG418

Replaces: Goodman®
B14010-18S

For further information refer to Product Sheet F174