SPCP SERIES

High Quality and Dependable Pump that is Designed to Remove Condensate Water from AC Systems, Heating Systems, Ice Machines, Drinking Fountains and Coolers.



• 22 Feet of Standard Lift @ 10 GPH

• Independent N.C. Safety Switch & Motor Shuts Down AC System to Prevent Condensate Overflow

- Three 1/4" Quick Connect Terminals are Provided for Easy Connection
- Independent N.O. Audible Alarm Switch Rated @ 80dB
- Specially Designed Leak Free Motor & Safety Float
- 3/8" Rubber Ball Check Valve
- Vibration Absorbing Feet
- Metal Side Mount Tabs, 11-1/2" on Center Between Tabs
- 3 Inlet Holes
- Includes 6' Power Cord

Sequence of Operation:

- 1. Pump Motor is Activated When More Than 2 1/4" of Water Collects in Tank
- 2. Pump Motor is Off when Less Than 1 1/4" of Water Collects in Tank
- 3. Pump Alarm on Safety Switch Opens When More Than 2 3/4" of Water Collects in Tank
- 4. Each Pump Cycle Drives 1/4 Gallon of Water Out of the Tank

Flow Rate Capacity

Lift Feet	1	5	10	15	20	22	24
GPH	99	87	69	48	20	10	0

CONDENSATE PUMP DRAIN TUBING

Part No.	Size
CPT3825	3/8 x 25'
CPT38100	3/8 x 100'

Part No.	SPCP115	SPCP230
hp	1/10hp	1/10hp
Voltage	120 VAC	230 VAC
Watts	80W	75W
Amps	1.45A	0.72A
Hertz	60Hz	60Hz
Motor Overload Protector	Yes	Yes
Whole Pump Height (In.)	7 1/4"	7 1/4"
Whole Pump Length (In.)	11 1/4"	11 1/4"
Whole Pump Width (In.)	5"	5"
Tank Size	1/2 Gal.	1/2 Gal.
Discharge	3/8" Barb	3/8" Barb
Tank Material	ABS	ABS
Impeller Material	Glassfiber filled PP	Glassfiber filled PP
Float Material	Polypropylene	Polypropylene
Shaft Material	S.S.304	S.S.304
Max. Temp. (°F)	110	110
Alarm	80 dB	80 dB
Auto Off with Dry Contacts	Yes	Yes
Float Activated	Yes	Yes

SCV1 CONDENSATE PUMP CHECK VALVE



Check Valve Accessory for SPCP Condensat Pumps

JV1 JONES VALVE CONDENSATE DRAIN CLEANOUT VALVE

ICC International Mechanical Code

307.2.5 cleanouts. Condensate drains shall be provided with a means to allow cleaning of the drain and clearing of blockages without having to cut or disassemble the piping.

• Attaches to a CO2 or Nitrogen Tank

- Durable, Schedule 40 PVC Material
- Condensate Line Size: 3/4"
- Hose Connection Size: 1/4" Male Flare (with Schrader)

UNIFORM MECHANICAL CODE (UMC)

312.3.1 Condensate drain lines shall be configured or provided with a clean out to permit the clearing of blockages and for maintenance without requiring the drain line to be cut.

• 1 Year Warranty

• U.S. Patent No. 8,375,977

6 Pack Counter Display

