Digital Multimeters

LT17A

The Biggest Bang for Your Buck

The LT series cover most parameters and ranges technicians need for HVACR applications. And to further expand testing capabilities, the leads connect directly to any Fieldpiece accessory head.



- Continuity indicator
- Type K thermocouple
- Bright, blue backlight
- Low ohm ranges
- Both mA and µA for testing flame rectifier diodes
- MIN/MAX function
- Probe storage
- Magnetic hanger and tilt stand

Current Clamp Head ACH4

- Measures AC Amps from 1A to 400A
- Accuracy: $1A-20A AC: \pm (1.5\% rdg + 0.2A)$ 20A-100A AC: ±(2.5% rdg + 0.3A) 100A-400A AC: ±(3.5% rdg + 0.5A)
- .91" (23mm) maximum conductor diameter



Electronic Handle for Accessory Heads EHDL1

Converts any Fieldpiece Accessory Head into a standalone instrument.

- MIN/MAX button
- Use with any Fieldpiece accessory head
- Hold button



Silicone Test Leads ASLS2

- High copper strands, silicone insulated test leads
- Basket style strain relief



Deluxe Silicone Test Leads ADLS2

 Same as the ASLS2 with the addition of removable probe tips for connection to accessory heads

Deluxe Test Lead Kit ADK7

- Silicone test leads, removable probe tips and alligator clips for grounding
- Includes molex tips







Included

- Deluxe silicone test leads ADLS2
- Short alligator lead extensions ASA2
- 400A amp clamp accessory ACH4
- Type K thermocouple ATB1
- Nylon case ANC5



Dual Alligator Clips ADA2

 Red and black vinyl insulated cables with small alligator clips on the ends. Each shorting cable is 3.5 feet long



