

## NANO Mini-Split Condensate Pumps

## Item#s MS-13X-1 and MS-13X-2

Hartell's Mini-Split Condensate Pump is designed for installations where space is limited. The ultra slim profile makes it ideal for air conditioning systems rated up to 50,000 BTU.

The reservoir/sensor fits inside of the air conditioning unit, while the pump can be mounted in a variety of locations, unobtrusive to indoor living space.

The Mini-Split is available in 115V (Model MS-13X-1) or 230V (Model MS-13X-2) and comes complete with low voltage alarm contacts and is designed for systems up to 24,000 BTU.

- For ductless (wall mounted) air-conditioning systems.
- Ultra low profile: 1-1/4".
- · LED diagnostics.
- Low voltage safety switch.
- Thermal overload protection.
- 6.5 ft. suction lift.
- 13 ft. discharge lift.
- 32 ft. horizontal run (@ 3ft. lift).
- Auxiliary switch contacts rated to 5 amp.
- 1 year warranty.



Item#	Mfr#	Motor	Auxiliary Switch	20 ft. Tubing	DIMENSIONS		
					н	w	D
	13	B FT. HEAD @	2.2 GAL./HR.	MAX. TEMPER	RATURE 140°F		
NANO-13X-1	861009	115V	YES	NO sensor only	2.60	1.00	1.26
NANO-13X-2	861010	230V	YES	NO sensor only	2.36	1.58	1.38