

APR5 ADJUSTABLE POTENTIAL RELAY



- Voltage Sensitive Relay
- Adjustable Pick-up Voltage
- Safety Time Out 1.0-1.5 Seconds
- Universal Mounting Bracket

APR5 & SUPR Specifications


Operating Voltage	110 – 270 VAC, Single Phase
Amperage	30 Amps
Motor Power Rating	up to 5 hp
Operating Position	Non-positional mounting
Terminals	Screw or push-on
Dimensions	1.75W x 2.25L x 1.50In

SUPR UNIVERSAL POTENTIAL RELAY



- Time Function Relay
- Start Time: 1.0-1.5 Seconds
- Universal Mounting Bracket

90XX SERIES POTENTIAL RELAYS



- Voltage Sensitive Relay
- Instant Re-start
- Safety Time Delay
- Use With Any Size Suitable Start Capacitor

Part No.	Continuous Coil Voltage	Pick-up Min.	Pick-Up Max.	Drop Max
9063	168	140	153	45
9064	395	242	272	140
9065	332	168	182	90
9066	395	204	233	130
9067	420	280	310	121
9068	502	314	342	135
9069	338	180	195	105
9070	332	285	305	85
9071	420	223	259	121

903X SERIES GENERAL PURPOSE SWITCHING RELAYS DOUBLE POLE- DOUBLE THROW



SUPCO® Part No.	Coil Voltage	FLA 120V	FLA 208V	FLA 240V	FLA 277V	HP	Essex® / RBM®	Honeywell®
90340	24	13.8	7.6	6.9	6	3/4	90-340	R8222D1014
90341	120	13.8	7.6	6.9	6	3/4	90-341	R4222D1013
90342	208/240	13.8	7.6	6.9	6	3/4	90-342	R4222N1021

FAN RELAYS



Part No.	Coil Voltage	Description	FLA 250V	LRA 250V
90290	24V	SPST	8	18
90291	120V	SPST	8	18
90292	240V	SPST	8	18
90293	24V	SPDT	8	18
90294	120V	SPDT	8	18
90295	240V	SPDT	8	18

Part No.	Coil Voltage	Description	FLA 120V	LRA 120V	FLA 250V	LRA 250V
90370	24V	SPDT	12	60	8	48
90372	120V	SPDT	12	60	8	48
90374	240V	SPDT	12	60	8	48
90380	24V	NO/NC	13	60	8	48
90382	120V	NO/NC	13	60	8	48
90384	240V	NO/NC	13	60	8	48