




36T ELECTRICAL RATING:
TYPICAL ELECTRICAL RATINGS TEMP RANGE: -40°F TO 350°F

GAS FURNACE LIMITS AND PLENUM THERMOSTATS


- Direct OEM Replacements
- Economical
- Use 36T Electrical Ratings
- Style 36TX01B
- 350°F Max Ambient Temperature



Volts (VAC)	Resistive (Non-Inductive)	Motor Rating (Inductive)		
		Full Load	Locked Rotor	Pilot Duty
120	15A	3A	12A	125VA
240	10A	1.5A	6A	125VA

Part No.	Description	Open	Close	Diff.	Board Width	Board Height	Insertion Length
SHL501	L170-40 SPST	170°	130°	40°	1.88"	2.8"	3.12"
SHL502	L180-30 SPST	180°	150°	30°	1.88"	2.8"	3.12"
SHL503	L190-40 SPST	190°	150°	40°	1.88"	2.8"	3.12"
SHL504	L240-40 SPST	240°	200°	40°	1.88"	2.8"	3.12"
SHL505	L140-40 SPST	140°	100°	40°	1.88"	2.8"	1.87"
SHL506	L170-40 SPST	170°	130°	40°	1.88"	2.8"	1.87"
SHL507	L140-30 SPST	140°	110°	30°	1.88"	2.8"	3.12"
SHL508	L190-20 SPST	190°	170°	20°	1.88"	2.8"	3.12"
SHL509	L240-30 SPST	240°	210°	30°	1.88"	2.8"	3.12"
SHL510	L150-20 SPST	150°	130°	20°	1.625"	1.44"	3.12"
SHL511	L160-20 SPST	160°	140°	20°	1.625"	1.44"	3.12"
SHL512	L170-20 SPST	170°	150°	20°	1.625"	1.44"	3.12"
SHL513	L170-40 SPST	170°	130°	40°	1.88"	2.94"	3.12"
SHL514	L180-40 SPST	180°	140°	40°	1.88"	2.94"	3.12"
SHL515	L200-40 SPST	200°	160°	40°	1.88"	2.94"	3.12"
SHL516	L210-40 SPST	210°	170°	40°	1.88"	2.94"	3.12"
SHL517	L220-50 SPST	220°	170°	50°	1.88"	2.94"	3.12"
SHL518	L250-40 SPST	250°	210°	40°	1.88"	2.94"	3.12"
SHL519	L155-30 SPST	155°	125°	30°	1.88"	2.8"	7.12"
SHL520	L100-20 SPST	100°	80°	20°	1.88"	2.8"	7"
SHL521	L200-20 SPST	200°	180°	20°	1.88"	2.8"	7"
SHL522	L160-20 SPST	160°	140°	20°	1.88"	2.8"	7"
SHL523	L130-20 SPST	130°	110°	20°	1.88"	2.8"	7"
SHL524	L170-20 SPST	170°	150°	20°	1.88"	2.8"	7"
SHL525	L180-20 SPST	180°	160°	20°	1.88"	2.8"	7"

TH181955 THERMOCOUPLE



- Designed to meet or exceed OEM specifications
- Single wire, metric thread
- Used on Vanguard® Units
- 24"
- Fits Gas Log Fireplaces

TH181975 THERMOCOUPLE



- Designed to meet or exceed OEM specifications
- Single wire, metric thread
- Used on York® and Nordyne® units
- 39"