

Gun Style IR Thermometer with Laser

SIG1

The SIG1 makes taking surface temperatures easy, accurate and fast. The narrow 10:1 field of view allows you to target smaller areas from further away. The backlight allows you to read the measurements in any light.

- 10:1 field of view
- Select °F or °C
- Range: -22°F to 1022°F
- Accuracy: $\pm 4^\circ\text{F}$ or 2% rdg, whichever is greater
- Resolution: 1°F
- Automatic data hold
- Backlight
- Auto Power Off (APO) to conserve battery life



Pocket Knife Style Stainless Steel Thermometer

SPK1

- Detent holds rod in 16 positions
- Easily hangs from thermostat, register, or a hole in flex duct
- Range: -58°F to 392°F
- MIN/MAX and Hold



In-duct Thermometer

SPK2

- Quick and easy in-duct measurements
- Hanging hook for hands free temps
- Fits easily in pocket
- Bright backlight
- Range: -58°F to 392°F



Water Resistant Stainless Steel Thermometer

SWT2

- MIN/MAX
- Accuracy: $\pm 1.8^\circ\text{F}$, -4°F to 392°F
- Resolution 0.1°F
- Range: -58°F to 392°F



SWT2 with cap off

Non-Contact Voltage Tester

SNCV1

- Detects live AC voltage without contact
- Bright LED and loud beeper
- Range: 24VAC to 440VAC
- Senses 24VAC for thermostat power
- Analog feel indicates strong and weak AC voltage fields



Megohmmeter

SMG5

- Helps predict compressor failure
- Great for preventative maintenance
- One handed testing
- Long probe tip for hard to reach terminals
- Bright backlight



IR Pocket Thermometer with LED Flashlight

SIL2

The SIL2 has great accuracy and a built-in bright LED flashlight that uses a separate AAA battery. The SIL2 looks like a pen in your pocket.

- 1:1 field of view
- Automatic data hold
- Select °F or °C
- Range: -27°F to 230°F
- Excellent accuracy: $\pm 1.5^\circ\text{F}$
- Resolution: 0.5°F
- Auto power off



Thermometer with Laser

SIR2

- 6:1 field of view
- MIN/MAX automatic data hold
- Select °F or °C
- Range: -27°F to 482°F
- Accuracy: $\pm 4^\circ\text{F}$ or 2% rdg, whichever is greater
- Resolution: 0.1°F
- Auto power off
- One-hand operation

