

PRO-SET® INSPECTION MIRRORS



TLMIR1
Circular Inspection Mirror

- Diameter 1.25" (32 mm)
- Length 7"~19.5" (178 mm ~ 495 mm)



TLMIR2
Circular Telescoping Mirror

- Diameter 2" (51 mm)
- Length 12"~18" (305 mm ~ 457 mm)



TLMIR3
Rectangular Telescoping Mirror

- Mirror size 2" X 3-1/2" (51 mm X 90 mm)
- Length 13-1/4" ~ 19-3/8" (286 mm X 492 mm)



TLMIR4
Oval Telescoping Mirror

- Mirror size 1" X 2" (25 mm X 51 mm)
- Length 9" X 18-1/8" (23 mm X 46 mm)

PRO-SET® OIL HAND PUMP



TLOP
Hand Oil Pump

- Removes oil from systems for recovery and conversion
- Adds oil to systems (2.6 oz /78 ml) per stroke against 200 psi pressure
- Universal stopper fits standard openings in 1, 2-1/2 and 5 gallon oil containers
- Automatic bleed valve equalizes pressure inside and outside of the oil container
- Use with alkyl-benzene, ester-based, polyol ester, mineral and synthetic oils. (not for use with ammonia laden oil)
- Suction transfer hose and fittings included

SOLENOID VALVE TROUBLESHOOTING MAGNET



TLMKC18
Solenoid Magnet

The TLMKC18 is designed to manually open solenoid valves by magnetically lifting the stem assembly and plunger. Simply slide the TLMKC18 over the valve's enclosing tube and the industrial grade magnets incorporated inside the rugged ABS plastic housing does the rest. It is an ideal tool for trouble shooting/servicing both direct connected or pilot operated 2-way solenoid, 3-way reclaim or 4-way reversing valves.

- 0.75"/18 mm opening fits all common manufactured valves

